

Brake Cleaner

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Issue date: 7/3/2024 Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : Brake Cleaner
Product code : ROK40384

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Main use category : Consumer use,Industrial use,Professional use

1.3. Details of the supplier of the safety data sheet

Ultimotive Ltd
4 Altbarn Close, Wyncolls Road
Severalls Business Park, Colchester, Essex.
CO4 9HY. United Kingdom
T +44 (0) 1206 855232
info@ultimotive.com

1.4. Emergency telephone number

Emergency number : +44 (0) 1206 855232

Country/Area	Organisation/Company	Address	Emergency number	Comment
United Kingdom	National Poisons Information Service (Birmingham Centre) City Hospital	Dudley Road B18 7QH	0344 892 0111	Only for healthcare professionals
United Kingdom	National Poisons Information Service (Cardiff Centre) University Hospital Llandough	Penlan Road CF64 2XX	0344 892 0111	Only for healthcare professionals
United Kingdom	National Poisons Information Service (Edinburgh Centre) Royal Infirmary of Edinburgh	Little France Crescent EH16 4SA	0344 892 0111	Only for healthcare professionals
United Kingdom	Guy's & St Thomas' Poisons Unit Medical Toxicology Unit, Guy's & St Thomas' Hospital Trust	Avonley Road SE14 5ER	+44 20 7188 7188	
United Kingdom	National Poisons Information Service (Newcastle Centre) Regional Drugs and Therapeutics Centre	16/17 Framlington Place Newcastle-upon-Tyne NE2 4AB	0344 892 0111	Only for healthcare professionals
United Kingdom	National Poisons Information Service (Belfast Centre) Royal Victoria Hospital	Grosvenor Road BT12 6BA	0344 892 0111	Only for healthcare professionals
United Kingdom	NHS 111/NHS 24/NHS Direct		111 0845 4647	or call a doctor

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 2 H225
Serious eye damage/eye irritation, Category 2 H319

Brake Cleaner

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Specific target organ toxicity — Single exposure, Category 3, H336

Narcosis

Hazardous to the aquatic environment — Chronic Hazard, H411

Category 2

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Highly flammable liquid and vapour. May cause drowsiness or dizziness. Causes serious eye irritation. Toxic to aquatic life with long lasting effects.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



Signal word (CLP)

: Danger

Contains

: PROPAN-2-OL; HYDROCARBONS C7 - C9 N ALKANES, ISOALKANES, CYCLICS; ethyl acetate; PROPYL ACETATE; 1-METHOXY-2-PROPANOL; 1-ETHOXYPROPAN-2-OL; PROPAN-1-OL

Hazard statements (CLP)

: H225 - Highly flammable liquid and vapour.
H319 - Causes serious eye irritation.
H336 - May cause drowsiness or dizziness.
H411 - Toxic to aquatic life with long lasting effects.

Precautionary statements (CLP)

: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.
No smoking.
P233 - Keep container tightly closed.
P240 - Ground and bond container and receiving equipment.
P241 - Use explosion-proof electrical/ventilating/lighting equipment.
P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.
P264 - Wash hands, forearms and face thoroughly after handling.
P271 - Use only outdoors or in a well-ventilated area.
P273 - Avoid release to the environment.
P280 - Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water .
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312 - Call a POISON CENTRE or doctor if you feel unwell.
P337+P313 - If eye irritation persists: Get medical advice/attention.
P370+P378 - In case of fire: Use media other than water to extinguish.
P391 - Collect spillage.
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
P403+P235 - Store in a well-ventilated place. Keep cool.
P405 - Store locked up.
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards

Contains no PBT/vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

Brake Cleaner

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
HYDROCARBONS C7 - C9 N ALKANES, ISOALKANES, CYCLICS	CAS-No.: 64742-49-0 EC-No.: 265-151-9 EC Index-No.: 649-328-00-1	<70	Flam. Liq. 2, H225 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
ethyl acetate	CAS-No.: 141-78-6 EC-No.: 205-500-4 EC Index-No.: 607-022-00-5	3.75 – 6.25	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
PROPYL ACETATE	CAS-No.: 109-60-4 EC-No.: 203-686-1 EC Index-No.: 607-024-00-6	3.75 – 6.25	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
PROPAN-2-OL	CAS-No.: 67-63-0 EC-No.: 200-661-7 EC Index-No.: 603-117-00-0	≥ 4.95	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
1-METHOXY-2-PROPANOL	CAS-No.: 107-98-2 EC-No.: 203-539-1 EC Index-No.: 603-064-00-3 REACH-no: 01-2119457435-35	≥ 2.5	Flam. Liq. 3, H226 STOT SE 3, H336
1-ETHOXYPROPAN-2-OL	CAS-No.: 1569-02-4 EC-No.: 216-374-5 EC Index-No.: 603-177-00-8	≥ 2.5	Flam. Liq. 3, H226 STOT SE 3, H336
METHANOL substance with a Community workplace exposure limit	CAS-No.: 67-56-1 EC-No.: 200-659-6 EC Index-No.: 603-001-00-X	≥ 2.5	Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation), H331 Acute Tox. 3 (Inhalation:dust,mist), H331 STOT SE 1, H370
PROPAN-1-OL	CAS-No.: 71-23-8 EC-No.: 200-746-9 EC Index-No.: 603-003-00-0	≥ 2.5	Flam. Liq. 2, H225 Eye Dam. 1, H318 STOT SE 3, H336

Specific concentration limits:

Name	Product identifier	Specific concentration limits (%)
METHANOL	CAS-No.: 67-56-1 EC-No.: 200-659-6 EC Index-No.: 603-001-00-X	(3 ≤ C ≤ 10) STOT SE 2; H371 (10 ≤ C < 100) STOT SE 1; H370

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Call a poison center or a doctor if you feel unwell.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Rinse skin with water/shower. Take off immediately all contaminated clothing.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

Brake Cleaner

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

First-aid measures for first aider : First aid workers will be equipped with suitable personal protective equipment.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : May cause drowsiness or dizziness.
Symptoms/effects after inhalation : Although no appropriate human or animal health effects data are known to exist, this material is expected to be an inhalation hazard.
Symptoms/effects after skin contact : None under normal conditions.
Symptoms/effects after eye contact : Eye irritation.
Symptoms/effects after ingestion : None under normal conditions.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Highly flammable liquid and vapour.
Explosion hazard : No direct explosion hazard.
Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Advice for firefighters

Firefighting instructions : Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Stop leak if safe to do so. Notify authorities if product enters sewers or public waters.
Absorb spillage to prevent material damage.

For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment.
Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures : Evacuate unnecessary personnel. Stop leak if safe to do so.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Collect spillage. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak without risks if possible.
Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.
Other information : Dispose of materials or solid residues at an authorized site.

Brake Cleaner

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed	: Not expected to present a significant hazard under anticipated conditions of normal use.
Precautions for safe handling	: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.
Hygiene measures	: Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Ground/bond container and receiving equipment.
Storage conditions	: Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.
Packaging materials	: Store always product in container of same material as original container.

Switzerland

Storage class (LK)	: LK 3 - Flammable liquids
--------------------	----------------------------

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

National occupational exposure and biological limit values

PROPAN-2-OL (67-63-0)	
Austria - Occupational Exposure Limits	
Local name	2-Propanol (Isopropanol; Isopropylalkohol)
MAK (OEL TWA)	500 mg/m ³
	200 ppm
MAK (OEL STEL)	2000 mg/m ³ (4x 30(Miw) min) (Kurzzeitwert für Großguss gilt bis 31.12.2013)
	2000 mg/m ³ (4x 15(Miw) min)
	800 ppm (4x 30(Miw) min) (Kurzzeitwert für Großguss gilt bis 31.12.2013)
	800 ppm (4x 15(Miw) min)
Regulatory reference	BGBl. II Nr. 156/2021
Belgium - Occupational Exposure Limits	
Local name	Alcool isopropylique # Isopropylalcohol
OEL TWA	500 mg/m ³
	200 ppm
OEL STEL	1000 mg/m ³
	400 ppm
Regulatory reference	Koninklijk besluit/Arrêté royal 19/11/2020

Brake Cleaner

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

PROPAN-2-OL (67-63-0)	
Bulgaria - Occupational Exposure Limits	
Local name	Изопропилов алкохол
OEL TWA	980 mg/m ³
OEL STEL	1225 mg/m ³
Regulatory reference	Наредба № 13 от 30.12.2003 г. за защита на работещите от рискове, свързани с експозиция на химични агенти при работа (изм. и доп. ДВ. бр. 47 от 2021 г., в сила от 04.06.2021 г.)
Croatia - Occupational Exposure Limits	
Local name	Propan-2-ol; izopropil-alkohol; izopropanol
GVI (OEL TWA)	999 mg/m ³
	400 ppm
KGVI (OEL STEL)	1250 mg/m ³
	500 ppm
Regulatory reference	Pravilnik o izmjenama i dopunama Pravilnika o graničnim vrijednostima izloženosti opasnim tvarima pri radu i o biološkim graničnim vrijednostima (NN 1/2021)
Croatia - Biological limit values	
Local name	Propan-2-ol
BLV	50 mg/l Karakteristični pokazatelj: aceton - Biološki uzorak: krv - Vrijeme uzorkovanja: na kraju radne smjene 0.86 µmol/l Karakteristični pokazatelj: aceton - Biološki uzorak: krv - Vrijeme uzorkovanja: na kraju radne smjene 50 mg/l Karakteristični pokazatelj: aceton - Biološki uzorak: mokraća - Vrijeme uzorkovanja: na kraju radne smjene 0.86 µmol/l Karakteristični pokazatelj: aceton - Biološki uzorak: mokraća - Vrijeme uzorkovanja: na kraju radne smjene
Regulatory reference	Pravilnik o izmjenama i dopunama Pravilnika o graničnim vrijednostima izloženosti opasnim tvarima pri radu i o biološkim graničnim vrijednostima (NN 91/2018)
Czech Republic - Occupational Exposure Limits	
Local name	2-Propanol (Isopropanol; Izopropylalkohol)
PEL (OEL TWA)	500 mg/m ³
	200 ppm
NPK-P (OEL C)	1000 mg/m ³
	400 ppm
Remark	I - dráždí sliznice (oči, dýchací cesty), respektive kůži.
Regulatory reference	Nariadení vlády č. 361/2007 Sb. (Předpis 195/2021 Sb.)
Denmark - Occupational Exposure Limits	
Local name	Isopropylalkohol (Isopropanol; 2-Propanol; sec-Propylalkohol)
OEL TWA	490 mg/m ³
	200 ppm
Regulatory reference	BEK nr 1426 af 28. juni 2021
Estonia - Occupational Exposure Limits	
Local name	2-propanool (isopropüülalkohol, isopropanool)
OEL TWA	350 mg/m ³

Brake Cleaner

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

PROPAN-2-OL (67-63-0)	
	150 ppm
OEL STEL	600 mg/m ³
	250 ppm
Regulatory reference	Vabariigi Valitsuse 20. märtsi 2001. a määruse nr 105 (RT I, 17.10.2019, 2); Vabariigi Valitsuse 10. märtsi 2019. a määruse nr 84
Finland - Occupational Exposure Limits	
Local name	2-Propanoli
HTP (OEL TWA)	500 mg/m ³
	200 ppm
HTP (OEL STEL)	620 mg/m ³
	250 ppm
Regulatory reference	HTP-ARVOT 2020 (Sosiaali- ja terveystieteiden ministeriö)
France - Occupational Exposure Limits	
Local name	Alcool isopropylique
VLE (OEL C/STEL)	980 mg/m ³
	400 ppm
Remark	Valeurs recommandées/admises
Regulatory reference	Circulaire du Ministère du travail (réf.: INRS ED 984, 2016)
Germany - Occupational Exposure Limits (TRGS 900)	
AGW (OEL TWA)	500 mg/m ³
	200 ppm
Peak exposure limitation factor	2(II)
Remark	DFG - Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe der DFG (MAK-Kommission); Y - Ein Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes (BGW) nicht befürchtet zu werden
Regulatory reference	TRGS900
Germany - Biological limit values (TRGS 903)	
Local name	Propan-2-ol
Biological limit value	25 mg/l Parameter: Aceton - Untersuchungsmaterial: B = Vollblut, U = Urin - Probenahmezeitpunkt: b) Expositionsende, bzw. Schichtende - Festlegung/Begründung: 11/2012 DFG 25 mg/l Parameter: Aceton - Untersuchungsmaterial: U = Urin - Probenahmezeitpunkt: b) Expositionsende, bzw. Schichtende - Festlegung/Begründung: 11/2012 DFG
Regulatory reference	TRGS 903
Greece - Occupational Exposure Limits	
Local name	Ισοπροπυλική αλκοόλη
OEL TWA	980 mg/m ³
	400 ppm
OEL STEL	1225 mg/m ³
	500 ppm

Brake Cleaner

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

PROPAN-2-OL (67-63-0)	
Regulatory reference	Π.Δ. 90/1999 - Προστασία της υγείας των εργαζομένων που εκτίθενται σε ορισμένους χημικούς παράγοντες κατά τη διάρκεια της εργασίας τους
Hungary - Occupational Exposure Limits	
Local name	IZOPROPIL-ALKOHOL
AK (OEL TWA)	500 mg/m³
CK (OEL STEL)	1000 mg/m³
Remark	b (Bőrön át is felszívódik), i (ingerlő anyag, amely izgatja a bőrt, nyálkahártyát, szemet vagy mindhármát); R (Azok az anyagok, amelyek egészségkárosító hatása RÖVID expozíció hatására jelentkezik)
Regulatory reference	5/2020. (II. 6.) ITM rendelet - A kémiai kóroki tényezők hatásának kitett munkavállalók egészségének és biztonságának védelméről
Hungary - Biological Exposure Indices	
Local name	Izopropil-alkohol (2-Propanol)
BEI	430 µmol/l Biológiai expozíciós (hatás) mutató: acetone - Biológiai minta: vizeletben - Mintavétel ideje: m.v. (műszak végén) 25 mg/l Biológiai expozíciós (hatás) mutató: acetone - Biológiai minta: vizeletben - Mintavétel ideje: m.v. (műszak végén)
Remark	A foglalkozási vegyi expozíció esetén ajánlott biológiai expozíciós és hatásmutatók határértékei
Regulatory reference	5/2020. (II. 6.) ITM rendelet - A kémiai kóroki tényezők hatásának kitett munkavállalók egészségének és biztonságának védelméről
Ireland - Occupational Exposure Limits	
Local name	Isopropyl alcohol [Propan-2-ol]
OEL TWA	200 ppm
OEL STEL	400 ppm
Remark	Sk (Substances which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body)
Regulatory reference	Chemical Agents Code of Practice 2021
Ireland - Biological limit values	
Local name	2-Propanol
BMGV	40 mg/l Parameter: acetone - Medium: urine - Sampling time: End of shift at end of workweek - Notations: B (Background), Ns (Non-specific)
Regulatory reference	Biological Monitoring Guidelines (HSA, 2011)
Latvia - Occupational Exposure Limits	
Local name	Izopropanols (2-propanols, izopropilspirts, 1-metil-1-etanols)
OEL TWA	350 mg/m³
OEL STEL	600 mg/m³
Regulatory reference	Ministru kabineta 2007. gada 15. maija noteikumiem Nr. 325 (Grozījumi Ministru kabineta 2011. gada 1. februārī noteikumiem Nr. 92)
Lithuania - Occupational Exposure Limits	
Local name	2-propanolis (izopropanolis, izopropilo alkoholis)
IPRV (OEL TWA)	350 mg/m³ 150 ppm

Brake Cleaner

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

PROPAN-2-OL (67-63-0)	
TPRV (OEL STEL)	600 mg/m ³
	250 ppm
Regulatory reference	LIETUVOS HIGIENOS NORMA HN 23:2011 (Nr. V-695/A1-272, 2018-06-12)
Poland - Occupational Exposure Limits	
Local name	Propan-2-ol (izopropylowy alkohol)
NDS (OEL TWA)	900 mg/m ³
NDSch (OEL STEL)	1200 mg/m ³
Remark	Skóra (Oznakowanie substancji notacją „skóra” oznacza, że wchłanianie substancji przez skórę może być tak samo istotne jak przy narażeniu drogą oddechową).
Regulatory reference	Dz. U. 2018 poz. 1286
Portugal - Occupational Exposure Limits	
Local name	2-Propanol (isopropanol ou álcool isopropílico)
OEL TWA	200 ppm
OEL STEL	400 ppm
Remark	A4 (Agente não classificável como carcinogénico no Homem); IBE (Índice biológico de exposição)
Regulatory reference	Norma Portuguesa NP 1796:2014
Portugal - Biological Exposure Indices	
Local name	2-Propanol
BEI	40 mg/l Parâmetro: Acetona - Meio: urina - Momento da amostragem: Fim do turno no fim da semana de trabalho - Notação: Vb (Valor basal), Ne (Não específico)
Regulatory reference	Norma Portuguesa NP 1796:2014
Romania - Occupational Exposure Limits	
Local name	Alcool izopropilic/2-Propanol
OEL TWA	200 mg/m ³
	81 ppm
OEL STEL	500 mg/m ³
	203 ppm
Regulatory reference	Hotărârea Guvernului nr. 1.218/2006 (Hotărârea nr. 53/2021)
Romania - Biological limit values	
Local name	Alcool izopropilic
BLV	50 mg/l Indicador biologic: Acetonă - Material biologic: urină - Momentul recoltării: sfârșit de schimb
Regulatory reference	Hotărârea Guvernului nr. 1.218/2006 (Hotărârea nr. 584/2018)
Slovakia - Occupational Exposure Limits	
Local name	Izopropylalkohol (propán-2-ol)
NPHV (OEL TWA)	500 mg/m ³
	200 ppm
NPHV (OEL STEL)	1000 mg/m ³
	400 ppm

Brake Cleaner

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

PROPAN-2-OL (67-63-0)	
Regulatory reference	Nariadenie vlády č. 355/2006 Z. z. (236/2020 Z. z.)
Slovenia - Occupational Exposure Limits	
Local name	propan-2-ol (izopropilalkohol; izopropanol)
OEL TWA	500 mg/m ³
	200 ppm
OEL STEL	1000 mg/m ³
	400 ppm
Remark	Y (Snovi, pri katerih ni nevarnosti za zarodek ob upoštevanju mejnih vrednosti in bat vrednosti), BAT (Biološka mejna vrednost)
Regulatory reference	Uradni list RS, št. 72/2021 z dne 11.5.2021
Slovenia - Biological limit values	
Local name	2 propanol
BLV	25 mg/l Parameter: aceton - Biološki vzorec: kri - Čas vzorčenja: ob koncu delovne izmene 25 mg/l Parameter: aceton - Biološki vzorec: urin - Čas vzorčenja: ob koncu delovne izmene
Regulatory reference	Uradni list RS, št. 72/2021 z dne 11.5.2021
Spain - Occupational Exposure Limits	
Local name	Isopropanol (Alcohol isopropílico)
VLA-ED (OEL TWA)	500 mg/m ³
	200 ppm
VLA-EC (OEL STEL)	1000 mg/m ³
	400 ppm
Remark	VLB® (Agente químico que tiene Valor Límite Biológico), s (Esta sustancia tiene prohibida total o parcialmente su comercialización y uso como fitosanitario y/o como biocida. Para una información detallada acerca de las prohibiciones consúltase: Base de datos de productos biocidas: http://www.msssi.gob.es/ciudadanos/productos.do?tipo=plaguicidas Base de datos de productos fitosanitarios http://www.magrama.gob.es/agricultura/pags/fitos/registro/fichas/pdf/Lista_sa.pdf).
Regulatory reference	Límites de Exposición Profesional para Agentes Químicos en España 2021. INSHT
Spain - Biological limit values	
Local name	Isopropanol (Alcohol isopropílico)
BLV	40 mg/l Parámetro: Acetona - Medio: Orina - Momento de muestreo: Final de la semana laboral - Notas: F (Fondo. El indicador está generalmente presente en cantidades detectables en personas no expuestas laboralmente. Estos niveles de fondo están considerados en el valor VLB), I (Significa que el indicador biológico es inespecífico puesto que puede encontrarse después de la exposición a otros agentes químicos)
Regulatory reference	Límites de Exposición Profesional para Agentes Químicos en España 2021. INSHT
Sweden - Occupational Exposure Limits	
Local name	Isopropanol
NGV (OEL TWA)	350 mg/m ³
	150 ppm
KTV (OEL STEL)	600 mg/m ³

Brake Cleaner

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

PROPAN-2-OL (67-63-0)	
	250 ppm
Remark	V (Vägledande korttidsgränsvärde ska användas som ett rekommenderat högsta värde som inte bör överskridas)
Regulatory reference	Hygieniska gränsvärden (AFS 2018:1)
United Kingdom - Occupational Exposure Limits	
Local name	Propan-2-ol
WEL TWA (OEL TWA)	999 mg/m³
	400 ppm
WEL STEL (OEL STEL)	1250 mg/m³
	500 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
Iceland - Occupational Exposure Limits	
Local name	2-Própanól (ísóprópanól, ísóprópýlalkóhól, sec-própýlalkóhól)
OEL TWA	490 mg/m³
	200 ppm
Remark	H (efnið getur auðveldlega borist inn í líkamann gegnum húð)
Regulatory reference	Reglugerð um mengunarmörk og aðgerðir til að draga úr mengun á vinnustöðum (Nr. 390/2009)
Norway - Occupational Exposure Limits	
Local name	2-propanol (Isopropanol)
Grenseverdi (OEL TWA)	245 mg/m³
	100 ppm
Regulatory reference	FOR-2021-06-28-2248
North Macedonia - Occupational Exposure Limits	
Local name	пропан-2-ол (изопропилалкохол; изопропанол)
OEL TWA	500 mg/m³
	200 ppm
KTV	4
Short time value [mg/m³]	2000 mg/m³
Short time value [ppm]	800 ppm
Remark	(KTV) краткотрајна вредност (КТВ) значи концентрација на опасни хемиски супстанции во воздухот на работното место внатре во зона на дишење, на која работникот без опасност по здравјето може да е изложен на покусо време. Изложеноста на краткотрајни вредности може да трае највеќе 15 минути и не смее да се повтори повеќе од четирипати во работната смена, при што меѓу две изложености на оваа концентрација мора да измине најмалку 60 минути. Краткотрајната вредност е изразена во mg/m³ или во ml/m³(ppm) а е дадена како многукратни дозволени пречекорувања на граничната вредност; (Y); (BAT) биолошка гранична вредност – праг на биолошка гранична вредност, што значи предупредување на опасна хемиска супстанца и нејзини метаболити во ткивата, телесните течности или издишувањето на воздухот, без оглед на тоа, дали опасната хемиска супстанца е внесена во организмот со вдишување, голтање или преку кожата

Brake Cleaner

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

PROPAN-2-OL (67-63-0)	
Regulatory reference	Правилник за минималните барања за безбедност и здравје при работа на вработени од ризици поврзани со изложување на хемиски супстанции („Службен весник на Република Македонија“ бр.46/10)
Switzerland - Occupational Exposure Limits	
Local name	2-Propanol / 2-Propanol [iso-Propylalkohol, Isopropanol, Isopropylalkohol]
MAK (OEL TWA)	500 mg/m ³
	200 ppm
KZGW (OEL STEL)	1000 mg/m ³
	400 ppm
Critical toxicity	VRS, Foie, SNC, Yeux / OAW, Leber, ZNS, Auge
Notation	SSc, B / SSc, B
Remark	INRS, NIOSH
Regulatory reference	www.suva.ch, 01.01.2021
Switzerland - BAT	
Local name	2-Propanol / 2-Propanol
BAT	25 mg/l (0.4 mmol/l; Paramètre biologique: Acétone; Substrat d'examen: Sang complet; Moment du prélèvement: Fin de l'exposition, de la période de travail.) / (0.4 mmol/l; Biologischer Parameter: Aceton; Untersuchungsmaterial: Vollblut; Probennahmezeitpunkt: Expositionsende, bzw. Schichtende.) 25 mg/l (0.4 mmol/l; Paramètre biologique: Acétone; Substrat d'examen: Urine; Moment du prélèvement: Fin de l'exposition, de la période de travail.) / (0.4 mmol/l; Biologischer Parameter: Aceton; Untersuchungsmaterial: Urin; Probennahmezeitpunkt: Expositionsende, bzw. Schichtende.)
Regulatory reference	Ordonnance 832.30 (OPA), article 50 al. 3, www.suva.ch/valeurs-limites / Verordnung 832.30 (VUV), Art. 50 Abs. 3, www.suva.ch/grenzwerte
METHANOL (67-56-1)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Methanol
IOEL TWA	200 ppm
Remark	Skin
Regulatory reference	COMMISSION DIRECTIVE 2006/15/EC
Austria - Occupational Exposure Limits	
Local name	Methanol (Methylalkohol)
MAK (OEL TWA)	260 mg/m ³
	200 ppm
MAK (OEL STEL)	1040 mg/m ³ (4x 15(Miw) min)
	800 ppm (4x 15(Miw) min)
Remark	H
Regulatory reference	BGBl. II Nr. 156/2021
Belgium - Occupational Exposure Limits	
Local name	Alcool méthylique # Methanol
OEL TWA	266 mg/m ³

Brake Cleaner

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

METHANOL (67-56-1)	
	200 ppm
OEL STEL	333 mg/m ³
	250 ppm
Remark	D: la mention "D" signifie que la résorption de l'agent, via la peau, les muqueuses ou les yeux, constitue une partie importante de l'exposition totale. Cette résorption peut se faire tant par contact direct que par présence de l'agent dans l'air. # D: de vermelding "D" betekent dat de opname van het agens via de huid, de slijmvliezen of de ogen een belangrijk deel van de totale blootstelling vormt. Deze opname kan het gevolg zijn van zowel direct contact als zijn aanwezigheid in de lucht.
Regulatory reference	Koninklijk besluit/Arrêté royal 19/11/2020
Bulgaria - Occupational Exposure Limits	
Local name	Метилов алкохол
OEL TWA	260 mg/m ³
	200 ppm
Remark	Кожа (възможна е значителна резорбция чрез кожата); • (Химични агенти, за които са определени гранични стойности във въздуха на работната среда за Европейската общност)
Regulatory reference	Наредба № 13 от 30.12.2003 г. за защита на работещите от рискове, свързани с експозиция на химични агенти при работа (изм. и доп. ДВ. бр. 47 от 2021 г., в сила от 04.06.2021 г.)
Croatia - Occupational Exposure Limits	
Local name	Metanol
GVI (OEL TWA)	260 mg/m ³
	200 ppm
Remark	Direktiva: 2006/15/EZ. Napomena: Koža (razvrstana kao tvar koja nadražuje kožu (H315))
Regulatory reference	Pravilnik o izmjenama i dopunama Pravilnika o graničnim vrijednostima izloženosti opasnim tvarima pri radu i o biološkim graničnim vrijednostima (NN 1/2021)
Croatia - Biological limit values	
Local name	Metanol
BLV	24.7 mmol/mol Creatinine Karakteristični pokazatelj: metanol - Biološki uzorak: mokraća - Vrijeme uzorkovanja: na kraju radne smjene 7 mg/g creatinine Karakteristični pokazatelj: metanol - Biološki uzorak: mokraća - Vrijeme uzorkovanja: na kraju radne smjene
Regulatory reference	Pravilnik o izmjenama i dopunama Pravilnika o graničnim vrijednostima izloženosti opasnim tvarima pri radu i o biološkim graničnim vrijednostima (NN 91/2018)
Cyprus - Occupational Exposure Limits	
Local name	Μεθανόλη
OEL TWA	260 mg/m ³
	200 ppm
Remark	δέρμα
Regulatory reference	Κανονισμοί του 2007 (Κ.Δ.Π. 295/2007)
Czech Republic - Occupational Exposure Limits	
Local name	Methanol (Methylalkohol)
PEL (OEL TWA)	250 mg/m ³

Brake Cleaner

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

METHANOL (67-56-1)	
	188 ppm
NPK-P (OEL C)	1000 mg/m ³
	751 ppm
Remark	D - při expozici se významně uplatňuje pronikání faktoru kůží, B - u látky je zaveden biologický expoziční test (BET) v moči nebo krvi.
Regulatory reference	Nařízení vlády č. 361/2007 Sb. (Předpis 195/2021 Sb.)
Czech Republic - Biological limit values	
Local name	Methanol (Methylalkohol)
BLV	15 mg/l Ukazatel: Methanol - Biološki uzorak: moči - Doba odběru: konec směny 0.47 mmol/l Ukazatel: Methanol - Biološki uzorak: moči - Doba odběru: konec směny
Regulatory reference	Vyhláška č. 107/2013 Sb. (kterou se mění vyhláška č. 432/2003 Sb.)
Denmark - Occupational Exposure Limits	
Local name	Methanol (Methylalkohol)
OEL TWA	260 mg/m ³
	200 ppm
Remark	E (betyder, at stoffet har en EF-grænseværdi); H (betyder, at stoffet kan optages gennem huden)
Regulatory reference	BEK nr 1426 af 28. juni 2021
Estonia - Occupational Exposure Limits	
Local name	Metanool (metüülalkohol)
OEL TWA	250 mg/m ³
	200 ppm
OEL STEL	350 mg/m ³
	250 ppm
Remark	A (Naha kaudu kergesti imenduv aine)
Regulatory reference	Vabariigi Valitsuse 20. märtsi 2001. a määruse nr 105 (RT I, 17.10.2019, 2); Vabariigi Valitsuse 10. märtsi 2019. a määruse nr 84
Finland - Occupational Exposure Limits	
Local name	Metanoli
HTP (OEL TWA)	270 mg/m ³
	200 ppm
HTP (OEL STEL)	330 mg/m ³
	250 ppm
Remark	Iho
Regulatory reference	HTP-ARVOT 2020 (Sosiaali- ja terveystieteiden ministeriö)
France - Occupational Exposure Limits	
Local name	Méthanol (alcool méthylique)
VME (OEL TWA)	260 mg/m ³
	200 ppm
Remark	Valeurs réglementaires contraignantes; risque de pénétration percutanée

Brake Cleaner

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

METHANOL (67-56-1)	
Regulatory reference	Article R4412-149 du Code du travail (réf.: INRS ED 984, 2016; Décret n° 2019-1487; Décret n° 2020-1546; Décret n°2021-434)
Germany - Occupational Exposure Limits (TRGS 900)	
AGW (OEL TWA)	130 mg/m ³
	100 ppm
Peak exposure limitation factor	2(II)
Remark	DFG - Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe der DFG (MAK-Kommission); EU - Europäische Union (Von der EU wurde ein Luftgrenzwert festgelegt: Abweichungen bei Wert und Spitzenbegrenzung sind möglich); H - hautresorptiv; Y - Ein Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes (BGW) nicht befürchtet zu werden
Regulatory reference	TRGS900
Germany - Biological limit values (TRGS 903)	
Local name	Methanol
Biological limit value	15 mg/l Parameter: Methanol - Untersuchungsmaterial: U = Urin - Probenahmezeitpunkt: b) Expositionsende, bzw. Schichtende, c) bei Langzeitexposition: am Schichtende nach mehreren vorangegangenen Schichten - Festlegung/Begründung: 11/2019 DFG
Regulatory reference	TRGS 903
Gibraltar - Occupational Exposure Limits	
Local name	Methanol
OEL TWA	260 mg/m ³
	200 ppm
Remark	Skin
Regulatory reference	Factories (Control of Chemical Agents at Work) Regulations 2003 (LN. 2018/181)
Greece - Occupational Exposure Limits	
Local name	Μεθανόλη
OEL TWA	260 mg/m ³
	200 ppm
OEL STEL	325 mg/m ³
	250 ppm
Remark	Η ένδειξη «δέρμα» στις οριακές τιμές επαγγελματικής έκθεσης επισημαίνει το ενδεχόμενο σημαντικής διείσδυσης μέσω του δέρματος.
Regulatory reference	Π.Δ. 90/1999 - Προστασία της υγείας των εργαζομένων που εκτίθενται σε ορισμένους χημικούς παράγοντες κατά τη διάρκεια της εργασίας τους
Hungary - Occupational Exposure Limits	
Local name	METANOL
AK (OEL TWA)	260 mg/m ³
Remark	b (Bőrön át is felszívódik), i (ingerlő anyag, amely izgatja a bőrt, nyálkahártyát, szemet vagy mindhármát); EU2 (2006/15/EK irányelvben közölt érték); R+T (Azok az anyagok, amelyek RÖVID és TARTÓS expozíciója is egészségkárosodást okoz)
Regulatory reference	5/2020. (II. 6.) ITM rendelet - A kémiai kóroki tényezők hatásának kitett munkavállalók egészségének és biztonságának védelméről

Brake Cleaner

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

METHANOL (67-56-1)	
Hungary - Biological Exposure Indices	
Local name	Metanol
BEI	30 mg/l Biológiai expozíció (hatás) mutató: metanol - Biológiai minta: vizeletben - Mintavétel ideje: m.v. (műszak végén) 940 µmol/l Biológiai expozíció (hatás) mutató: metanol - Biológiai minta: vizeletben - Mintavétel ideje: m.v. (műszak végén)
Regulatory reference	5/2020. (II. 6.) ITM rendelet - A kémiai kóroki tényezők hatásának kitett munkavállalók egészségének és biztonságának védelméről
Ireland - Occupational Exposure Limits	
Local name	Methanol [Methyl alcohol]
OEL TWA	260 mg/m ³
	200 ppm
Remark	Sk (Substances which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body), IOELV (Indicative Occupational Exposure Limit Values)
Regulatory reference	Chemical Agents Code of Practice 2021
Ireland - Biological limit values	
Local name	Methanol
BMGV	15 mg/l Parameter: methanol - Medium: urine - Sampling time: End of shift - Notations: B (Background), Ns (Non-specific)
Regulatory reference	Biological Monitoring Guidelines (HSA, 2011)
Italy - Occupational Exposure Limits	
Local name	Metanolo
OEL TWA	260 mg/m ³
	200 ppm
Remark	Cute
Regulatory reference	Allegato XXXVIII del D.Lgs. 9 aprile 2008, n. 81 e s.m.i.
Latvia - Occupational Exposure Limits	
Local name	Metanols (metilspirts, karbinols)
OEL TWA	260 mg/m ³
	200 ppm
Remark	Āda
Regulatory reference	Ministru kabineta 2007. gada 15. maija noteikumi Nr. 325
Lithuania - Occupational Exposure Limits	
Local name	Metanolis (metilo alkoholis)
IPRV (OEL TWA)	260 mg/m ³
	200 ppm
Remark	O (medžiaga į organizmą gali prasiskverbti pro nepažeistą odą)
Regulatory reference	LIETUVOS HIGIENOS NORMA HN 23:2011 (Nr. V-695/A1-272, 2018-06-12)
Luxembourg - Occupational Exposure Limits	
Local name	Méthanol

Brake Cleaner

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

METHANOL (67-56-1)	
OEL TWA	260 mg/m ³
	200 ppm
Remark	Peau
Regulatory reference	Mémorial A N° 226 de 2021 concernant la protection de la sécurité et de la santé des salariés contre les risques liés à des agents chimiques sur le lieu de travail
Malta - Occupational Exposure Limits	
Local name	Methanol
OEL TWA	260 mg/m ³
	200 ppm
Remark	Skin # Ġilda
Regulatory reference	S.L.424.24 - Chemical Agents at Work Regulations (L.N.57 of 2018)
Netherlands - Occupational Exposure Limits	
Local name	Methanol
TGG-8u (OEL TWA)	133 mg/m ³
Remark	H (Huidopname) Stoffen die relatief gemakkelijk door de huid kunnen worden opgenomen, hetgeen een substantiële bijdrage kan betekenen aan de totale inwendige blootstelling, hebben in de lijst een H-aanduiding. Bij deze stoffen moeten naast maatregelen tegen inademing ook adequate maatregelen ter voorkoming van huidcontact worden genomen.
Regulatory reference	Arbeidsomstandighedenregeling 2021
Poland - Occupational Exposure Limits	
Local name	Metanol (metylowy alkohol)
NDS (OEL TWA)	100 mg/m ³
NDSch (OEL STEL)	300 mg/m ³
Remark	Skóra (Oznakowanie substancji notacją „skóra” oznacza, że wchłanianie substancji przez skórę może być tak samo istotne jak przy narażeniu drogą oddechową).
Regulatory reference	Dz. U. 2018 poz. 1286
Portugal - Occupational Exposure Limits	
Local name	Metanol (Álcool metílico)
OEL TWA	200 ppm
OEL STEL	250 ppm
Remark	P (Toxicidade percutânea); IBE (Índice biológico de exposição)
Regulatory reference	Norma Portuguesa NP 1796:2014
Portugal - Biological Exposure Indices	
Local name	Metanol
BEI	15 mg/l Parâmetro: Metanol - Meio: urina - Momento da amostragem: Fim do turno - Notação: Vb (Valor basal), Ne (Não específico)
Regulatory reference	Norma Portuguesa NP 1796:2014
Romania - Occupational Exposure Limits	
Local name	Metanol/Alcool metilic
OEL TWA	260 mg/m ³
	200 ppm

Brake Cleaner

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

METHANOL (67-56-1)	
Remark	P - posibilitatea unei penetrări cutanate importante
Regulatory reference	Hotărârea Guvernului nr. 1.218/2006 (Hotărârea nr. 53/2021)
Romania - Biological limit values	
Local name	Alcool metilic
BLV	6 mg/l Indicator biologic: Metanol - Material biologic: urină - Momentul recoltării: sfârșit de schimb
Regulatory reference	Hotărârea Guvernului nr. 1.218/2006 (Hotărârea nr. 584/2018)
Serbia - Occupational Exposure Limits	
Local name	метанол
OEL TWA	260 mg/m ³
	200 ppm
Remark	EU** – напомена да се ради о хемијским материјама за које су утврђене индикативне граничне вредности изложености према Директиви 2006/15/ЕЗ (друга листа); К – напомена да хемијска материја може штетно деловати на кожу
Regulatory reference	ПРАВИЛНИК о превентивним мерама за безбедан и здрав рад при излагању хемијским материјама („Службени гласник РС”, бр. 106/09 и 117/17)
Slovakia - Occupational Exposure Limits	
Local name	Metylalkohol (metanol)
NPHV (OEL TWA)	260 mg/m ³
	200 ppm
Remark	K - znamená, že faktor môže byť ľahko absorbovaný kožou
Regulatory reference	Nariadenie vlády č. 355/2006 Z. z. (236/2020 Z. z.)
Slovakia - Biological limit values	
Local name	Metanol
BLV	30 µg/l Zisťovaný faktor: Metanol - Vyšetovaný materiál: moč - Čas odberu vzorky: c) pri dlhodobej expozícii; po viacerých pracovných zmenách, b) koniec expozície alebo pracovnej zmeny
Regulatory reference	Nariadenie vlády č. 355/2006 Z. z. (Zmena: 471/2011 Z.z.)
Slovenia - Occupational Exposure Limits	
Local name	metanol (metilalkohol)
OEL TWA	260 mg/m ³
	200 ppm
OEL STEL	1040 mg/m ³
	800 ppm
Remark	K (Lastnost lažjega prehajanja snovi v organizem skozi kožo), Y (Snovi, pri katerih ni nevarnosti za zarodek ob upoštevanju mejnih vrednosti in bat vrednosti), BAT (Biološka mejna vrednost), EU
Regulatory reference	Uradni list RS, št. 72/2021 z dne 11.5.2021
Slovenia - Biological limit values	
Local name	metanol

Brake Cleaner

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

METHANOL (67-56-1)	
BLV	15 mg/l Parameter: metanol - Biološki vzorec: urin - Čas vzorčenja: ob koncu delovne izmene, pri dolgotrajni izpostavljenosti: ob koncu delovne izmene po več zaporednih delavnikih
Regulatory reference	Uradni list RS, št. 72/2021 z dne 11.5.2021
Spain - Occupational Exposure Limits	
Local name	Metanol (Alcohol metílico)
VLA-ED (OEL TWA)	266 mg/m ³
	200 ppm
Remark	Vía dérmica (Indica que, en las exposiciones a esta sustancia, la aportación por la vía cutánea puede resultar significativa para el contenido corporal total si no se adoptan medidas para prevenir la absorción. En estas situaciones, es aconsejable la utilización del control biológico para poder cuantificar la cantidad global absorbida del contaminante), VLB® (Agente químico que tiene Valor Límite Biológico), VLI (Agente químico para el que la U.E. estableció en su día un valor límite indicativo).
Regulatory reference	Límites de Exposición Profesional para Agentes Químicos en España 2021. INSHT
Spain - Biological limit values	
Local name	Metanol (Alcohol metílico)
BLV	15 mg/l Parámetro: Metanol - Medio: Orina - Momento de muestreo: Final de la jornada laboral - Notas: F (Fondo. El indicador está generalmente presente en cantidades detectables en personas no expuestas laboralmente. Estos niveles de fondo están considerados en el valor VLB), I (Significa que el indicador biológico es inespecífico puesto que puede encontrarse después de la exposición a otros agentes químicos)
Regulatory reference	Límites de Exposición Profesional para Agentes Químicos en España 2021. INSHT
Sweden - Occupational Exposure Limits	
Local name	Metanol
NGV (OEL TWA)	250 mg/m ³
	200 ppm
KTV (OEL STEL)	350 mg/m ³
	250 ppm
Remark	H (Ämnet kan lätt upptas genom huden. Det föreskrivna gränsvärdet bedöms ge tillräckligt skydd endast under förutsättning att huden är skyddad mot exponering för ämnet ifråga); V (Vägledande kortidsgränsvärde ska användas som ett rekommenderat högsta värde som inte bör överskridas)
Regulatory reference	Hygieniska gränsvärden (AFS 2018:1)
United Kingdom - Occupational Exposure Limits	
Local name	Methanol
WEL TWA (OEL TWA)	266 mg/m ³
	200 ppm
WEL STEL (OEL STEL)	333 mg/m ³
	250 ppm
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

Brake Cleaner

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

METHANOL (67-56-1)	
Iceland - Occupational Exposure Limits	
Local name	Metanól (metýlalkóhól, tréspíritus)
OEL TWA	260 mg/m ³
	200 ppm
Remark	H (efnið getur auðveldlega borist inn í líkamann gegnum húð)
Regulatory reference	Reglugerð um mengunarmörk og aðgerðir til að draga úr mengun á vinnustöðum (Nr. 390/2009)
Norway - Occupational Exposure Limits	
Local name	Metanol
Grenseverdi (OEL TWA)	130 mg/m ³
	100 ppm
Remark	H: Kjemikalier som kan tas opp gjennom huden; E: EU har en veiledende grenseverdi og/eller anmerkning for stoffet.
Regulatory reference	FOR-2021-06-28-2248
North Macedonia - Occupational Exposure Limits	
Local name	метанол (метилалкохол)
OEL TWA	260 mg/m ³
	200 ppm
Remark	(K) својство на полесно пренесување на супстанците во организмот преку кожата; (BAT) биолошка гранична вредност – праг на биолошка гранична вредност, што значи предупредување на опасна хемиска супстанца и нејзини метаболити во ткивата, телесните течности или издишувањето на воздухот, без оглед на тоа, дали опасната хемиска супстанца е внесена во организмот со вдишување, голтање или преку кожата; (EU) European Union – гранична вредност, определена на ниво на Европската унија
Regulatory reference	Правилник за минималните барања за безбедност и здравје при работа на вработени од ризици поврзани со изложување на хемиски супстанции („Службен весник на Република Македонија“ бр.46/10)
Switzerland - Occupational Exposure Limits	
Local name	Méthanol / Methanol [Methylalkohol]
MAK (OEL TWA)	260 mg/m ³
	200 ppm
KZGW (OEL STEL)	520 mg/m ³
	400 ppm
Critical toxicity	SNC / ZNS
Notation	R, SSc, B / H, SSc, B
Remark	INRS, NIOSH
Regulatory reference	www.suva.ch, 01.01.2021
Switzerland - BAT	
Local name	Méthanol / Methanol

Brake Cleaner

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

METHANOL (67-56-1)	
BAT	30 mg/l (936 µmol/l; Paramètre biologique: Méthanol; Substrat d'examen: Urine; Moment du prélèvement: Fin de l'exposition, de la période de travail. Exposition de longue durée: après plusieurs périodes de travail.) / (936 µmol/l; Biologischer Parameter: Methanol; Untersuchungsmaterial: Urin; Probennahmezeitpunkt: Expositionsende, bzw. Schichtende. Bei Langzeitexposition: nach mehreren vorangegangenen Schichten.)
Regulatory reference	Ordonnance 832.30 (OPA), article 50 al. 3, www.suva.ch/valeurs-limites / Verordnung 832.30 (VUV), Art. 50 Abs. 3, www.suva.ch/grenzwerte

8.2. Exposure controls

Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

Personal protection equipment

Personal protective equipment:

Wear recommended personal protective equipment.

Personal protective equipment symbol(s):



Eye and face protection

Eye protection:

Safety glasses

Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Protective gloves

Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Not available
Odour	: Not available
Odour threshold	: Not available
Melting point	: Not applicable
Freezing point	: Not available
Boiling point	: Not available
Flammability	: Not available
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: Not available
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: Not available

Brake Cleaner

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Viscosity, kinematic	: Not available
Solubility	: Not available
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50 °C	: Not available
Density	: Not available
Relative density	: Not available
Relative vapour density at 20 °C	: Not available
Particle characteristics	: Not applicable

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Highly flammable liquid and vapour.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

PROPAN-2-OL (67-63-0)

LD50 oral rat	5840 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
---------------	--

HYDROCARBONS C7 - C9 N ALKANES, ISOALKANES, CYCLICS (64742-49-0)

LD50 dermal rat	2800 – 3100 mg/kg bodyweight Animal: rat, Remarks on results: other:
LC50 Inhalation - Rat	> 23.3 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)

1-METHOXY-2-PROPANOL (107-98-2)

LD50 oral	11700 mg/kg
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: EU Method B.3 (Acute Toxicity (Dermal))

PROPAN-1-OL (71-23-8)

LD50 dermal rabbit	4032 mg/kg bodyweight Animal: rabbit, Animal sex: male, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Remarks on results: other:, 95% CL: 2720 - 5968
--------------------	--

Brake Cleaner

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: May cause drowsiness or dizziness.

PROPAN-2-OL (67-63-0)

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

HYDROCARBONS C7 - C9 N ALKANES, ISOALKANES, CYCLICS (64742-49-0)

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

ethyl acetate (141-78-6)

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

PROPYL ACETATE (109-60-4)

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

1-METHOXY-2-PROPANOL (107-98-2)

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

1-ETHOXYPROPAN-2-OL (1569-02-4)

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

METHANOL (67-56-1)

STOT-single exposure	Causes damage to organs.
----------------------	--------------------------

PROPAN-1-OL (71-23-8)

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

STOT-repeated exposure : Not classified

HYDROCARBONS C7 - C9 N ALKANES, ISOALKANES, CYCLICS (64742-49-0)

NOAEC (inhalation, rat, vapour, 90 days)	24.3 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)
--	---

1-METHOXY-2-PROPANOL (107-98-2)

LOAEL (oral, rat, 90 days)	2757 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)
NOAEL (oral, rat, 90 days)	919 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)
NOAEL (dermal, rat/rabbit, 90 days)	> 1000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)

PROPAN-1-OL (71-23-8)

LOAEL (oral, rat, 90 days)	≤ 0.8 mg/kg bodyweight Animal: rat, Animal sex: male
NOAEL (oral, rat, 90 days)	> 0.003 mg/kg bodyweight Animal: rat, Animal sex: male, Remarks on results: not determinable due to absence of adverse toxic effects
NOAEC (inhalation, rat, vapour, 90 days)	8 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study), Guideline: other:, Guideline: other:
NOAEL (subchronic, oral, animal/male, 90 days)	> 4000 mg/kg bodyweight Animal: mouse, Animal sex: male, Remarks on results: not determinable due to absence of adverse toxic effects

Aspiration hazard : Not classified

Brake Cleaner

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

HYDROCARBONS C7 - C9 N ALKANES, ISOALKANES, CYCLICS (64742-49-0)

Viscosity, kinematic	0.715 – 0.786 mm²/s Temp.: 'other:' Parameter: 'kinematic viscosity (in mm²/s)'
----------------------	---

1-METHOXY-2-PROPANOL (107-98-2)

Viscosity, kinematic	1.848 mm²/s
----------------------	-------------

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: Toxic to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Toxic to aquatic life with long lasting effects.

PROPAN-2-OL (67-63-0)

LC50 - Fish [1]	10000 mg/l Test organisms (species): Pimephales promelas
LC50 - Fish [2]	9640 mg/l Test organisms (species): Pimephales promelas

HYDROCARBONS C7 - C9 N ALKANES, ISOALKANES, CYCLICS (64742-49-0)

LOEC (chronic)	0.32 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	0.17 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

1-METHOXY-2-PROPANOL (107-98-2)

EC50 - Other aquatic organisms [1]	2954 mg/l Test organisms (species): other aquatic crustacea:
------------------------------------	--

PROPAN-1-OL (71-23-8)

LC50 - Fish [1]	4555 mg/l Test organisms (species): Pimephales promelas
EC50 - Crustacea [1]	3644 mg/l Test organisms (species): Daphnia magna

12.2. Persistence and degradability

Brake Cleaner

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

PROPAN-2-OL (67-63-0)

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

HYDROCARBONS C7 - C9 N ALKANES, ISOALKANES, CYCLICS (64742-49-0)

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

ethyl acetate (141-78-6)

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

PROPYL ACETATE (109-60-4)

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

1-METHOXY-2-PROPANOL (107-98-2)

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

Brake Cleaner

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

1-ETHOXYPROPAN-2-OL (1569-02-4)	
Persistence and degradability	Not rapidly degradable
METHANOL (67-56-1)	
Persistence and degradability	Not rapidly degradable
PROPAN-1-OL (71-23-8)	
Persistence and degradability	Not rapidly degradable

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste)	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations	: Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	: Disposal must be done according to official regulations.
Additional information	: Flammable vapours may accumulate in the container. Do not re-use empty containers.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
UN 1219	UN 1219	UN 1219	UN 1219	UN 1219
14.2. UN proper shipping name				
ISOPROPANOL (ISOPROPYL ALCOHOL)	ISOPROPANOL (ISOPROPYL ALCOHOL)	Isopropanol	ISOPROPANOL (ISOPROPYL ALCOHOL)	ISOPROPANOL (ISOPROPYL ALCOHOL)
Transport document description				
UN 1219 ISOPROPANOL (ISOPROPYL ALCOHOL), 3, II, (D/E), ENVIRONMENTALLY HAZARDOUS	UN 1219 ISOPROPANOL (ISOPROPYL ALCOHOL), 3, II, MARINE POLLUTANT/ENVIRONME NTALLY HAZARDOUS (12°C c.c.)	UN 1219 Isopropanol, 3, II, ENVIRONMENTALLY HAZARDOUS	UN 1219 ISOPROPANOL (ISOPROPYL ALCOHOL), 3, II, ENVIRONMENTALLY HAZARDOUS	UN 1219 ISOPROPANOL (ISOPROPYL ALCOHOL), 3, II, ENVIRONMENTALLY HAZARDOUS

Brake Cleaner

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ADR	IMDG	IATA	ADN	RID
14.3. Transport hazard class(es)				
3 	3 	3 	3 	3
14.4. Packing group				
II	II	II	II	II
14.5. Environmental hazards				
Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes EmS-No. (Fire): F-E EmS-No. (Spillage): S-D	Dangerous for the environment: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes
No supplementary information available				

14.6. Special precautions for user

Overland transport

Classification code (ADR)	: F1
Special provisions (ADR)	: 601
Limited quantities (ADR)	: 1I
Excepted quantities (ADR)	: E2
Packing instructions (ADR)	: P001, IBC02, R001
Mixed packing provisions (ADR)	: MP19
Portable tank and bulk container instructions (ADR)	: T4
Portable tank and bulk container special provisions (ADR)	: TP1
Tank code (ADR)	: LGBF
Vehicle for tank carriage	: FL
Transport category (ADR)	: 2
Special provisions for carriage - Operation (ADR)	: S2, S20
Hazard identification number (Kemler No.)	: 33
Orange plates	:
Tunnel restriction code (ADR)	: D/E
EAC code	: •2YE

Transport by sea

Limited quantities (IMDG)	: 1 L
Excepted quantities (IMDG)	: E2
Packing instructions (IMDG)	: P001
IBC packing instructions (IMDG)	: IBC02
Tank instructions (IMDG)	: T4
Tank special provisions (IMDG)	: TP1
Stowage category (IMDG)	: B
Flash point (IMDG)	: 12°C c.c.
Properties and observations (IMDG)	: Colourless, mobile liquid. Flashpoint: 12°C c.c. Explosive limits: 2% to 12% Miscible with water.

Air transport

PCA Excepted quantities (IATA)	: E2
PCA Limited quantities (IATA)	: Y341
PCA limited quantity max net quantity (IATA)	: 1L

Brake Cleaner

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

PCA packing instructions (IATA)	: 353
PCA max net quantity (IATA)	: 5L
CAO packing instructions (IATA)	: 364
CAO max net quantity (IATA)	: 60L
Special provisions (IATA)	: A180
ERG code (IATA)	: 3L

Inland waterway transport

Classification code (ADN)	: F1
Special provisions (ADN)	: 601
Limited quantities (ADN)	: 1 L
Excepted quantities (ADN)	: E2
Carriage permitted (ADN)	: T
Equipment required (ADN)	: PP, EX, A
Ventilation (ADN)	: VE01
Number of blue cones/lights (ADN)	: 1

Rail transport

Classification code (RID)	: F1
Special provisions (RID)	: 601
Limited quantities (RID)	: 1L
Excepted quantities (RID)	: E2
Packing instructions (RID)	: P001, IBC02, R001
Mixed packing provisions (RID)	: MP19
Portable tank and bulk container instructions (RID)	: T4
Portable tank and bulk container special provisions (RID)	: TP1
Tank codes for RID tanks (RID)	: LGBF
Transport category (RID)	: 2
Colis express (express parcels) (RID)	: CE7
Hazard identification number (RID)	: 33

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU-Regulations

REACH Annex XVII (Restriction List)

Contains no REACH substances with Annex XVII restrictions

REACH Annex XIV (Authorisation List)

Contains no REACH Annex XIV substances

REACH Candidate List (SVHC)

Contains no substance on the REACH candidate list

PIC Regulation (Prior Informed Consent)

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

POP Regulation (Persistent Organic Pollutants)

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

Ozone Regulation (1005/2009)

Contains no substance subject to REGULATION (EU) No 1005/2009 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 September 2009 on substances that deplete the ozone layer.

Brake Cleaner

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Dual-Use Regulation (428/2009)

Contains no substance subject to the COUNCIL REGULATION (EC) No 428/2009 of 5 May 2009 setting up a Community regime for the control of exports, transfer, brokering and transit of dual-use items.

Explosives Precursors Regulation (2019/1148)

Contains no substance subject to Regulation (EU) 2019/1148 of the European Parliament and of the Council of 20 June 2019 on the marketing and use of explosives precursors.

Drug Precursors Regulation (273/2004)

Contains no substance subject to Regulation (EC) 273/2004 of the European Parliament and of the Council of 11 February 2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances.

National regulations

France

Occupational diseases	
Code	Description
RG 84	Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide

Germany

Employment restrictions	: Observe restrictions according Act on the Protection of Working Mothers (MuSchG). Observe restrictions according Act on the Protection of Young People in Employment (JArbSchG).
Water hazard class (WGK)	: WGK 3, Highly hazardous to water (Classification according to AwSV, Annex 1).
Hazardous Incident Ordinance (12. BImSchV)	: Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

Netherlands

SZW-lijst van kankerverwekkende stoffen	: HYDROCARBONS C7 - C9 N ALKANES, ISOALKANES, CYCLICS is listed
SZW-lijst van mutagene stoffen	: HYDROCARBONS C7 - C9 N ALKANES, ISOALKANES, CYCLICS is listed
SZW-lijst van reprotoxische stoffen – Borstvoeding	: None of the components are listed
SZW-lijst van reprotoxische stoffen – Vruchtbaarheid	: None of the components are listed
SZW-lijst van reprotoxische stoffen – Ontwikkeling	: None of the components are listed

Denmark

Danish National Regulations	: Young people below the age of 18 years are not allowed to use the product Pregnant/breastfeeding women working with the product must not be in direct contact with the product
-----------------------------	---

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)

Brake Cleaner

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:	
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disruptor

Full text of H- and EUH-statements:	
Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3
Acute Tox. 3 (Inhalation)	Acute toxicity (inhal.), Category 3
Acute Tox. 3 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2

Brake Cleaner

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:	
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H301	Toxic if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H336	May cause drowsiness or dizziness.
H370	Causes damage to organs.
H371	May cause damage to organs.
H411	Toxic to aquatic life with long lasting effects.
STOT SE 1	Specific target organ toxicity — single exposure, Category 1
STOT SE 2	Specific target organ toxicity — Single exposure, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.