

Product Information

MOVING YOUR WORLD



SILKOLENE FOAM FILTER KIT

Advanced Motorcycle Foam Filter oil, Filter Cleaner and Service Kit

Description

The Silkolene Foam Filter Service kit comprises of 1L of Silkolene Foam Filter oil, 4L of Silkolene Foam filter cleaner, 2 buckets a strainer and some protective gloves. SILKOLENE FOAM FILTER OIL is an advanced coating treatment designed to improve the efficiency of foam air filters. The product contains additives which provide a hyper-tacky surface which resists the ingress of the most pervasive sand, dust and water without affecting engine breathing. SILKOLENE FOAM FILTER OIL gives excellent dust retention without restricting airflow and is a low viscosity treatment easily achieving complete coverage. As the solvent evaporates the product becomes more viscous and forms the highly tacky /adhesive surface coating. SILKOLENE FOAM FILTER OIL should be renewed regularly for optimum protection using the method outlined under directions for use. NOTE: Replace screw top immediately after use (to avoid evaporation). SILKOLENE FOAM FILTER CLEANER is a highly effective, water rinsable cleaner formulated specifically for cleaning foam filters. SILKOLENE FOAM FILTER CLEANER easily removes dirt, dust, soil, grease and grime, extending the life of filters. SILKOLENE FOAM FILTER CLEANER can also be used for the degreasing of engine components. SILKOLENE FOAM FILTER OIL has been developed to provide outstanding engine protection even in the most severe conditions. It reduces the risk of breakdown and helps extend engine life. This advanced formula is free from chlorinated solvents and is compatible with all foam filter construction materials and adhesives.

Cleaning – Immerse filter in SILKOLENE FOAM FILTER CLEANER and agitate to remove dirt and contaminated oil. Rinse with water, squeeze out and allow to dry. Oiling - Soak thoroughly in SILKOLENE FOAM FILTER OIL, squeeze or drain to remove excess and allow to dry to a tacky consistency before re-installing in the airbox and running the engine.

Specifications

- -

Approvals

- -

FUCHS Recommendations

- -

Application

DIRECTIONS FOR USE:

2023-11-14 11:14:27, SILKOLENE FOAM FILTER KIT_CP1003630_EN_GB20_TC01_P001.pdf

Page 1

Product Information

MOVING YOUR WORLD



Notes

The information contained in this product information is based on the experience and know-how of FUCHS LUBRICANTS (UK) plc in the development and manufacturing of lubricants and represents the current state-of-the-art. The performance of our products can be influenced by a series of factors, especially the specific use, the method of application, the operational environment, component pre-treatment, possible external contamination, etc. For this reason, universally valid statements about the function of our products are not possible.

Our products must not be used in aircraft or spacecraft. Our products may be used in manufacture of components for aircraft or spacecraft if they are removed without residue from the components prior to assembly into the aircraft or spacecraft.

The information given in this product information represents general, non-binding guidelines. No warranty expressed or implied is given concerning the properties of the product or its suitability for any given application. We therefore recommend that you consult a FUCHS LUBRICANTS (UK) plc application engineer to discuss application conditions and the performance criteria of the products before the product is used. It is the responsibility of the user to test the functional suitability of the product and to use it with the corresponding care.

Our products undergo continuous improvement. We therefore retain the right to change our product program, the products, and their manufacturing processes as well as all details of our product information sheets at any time and without warning, unless otherwise provided in customer-specific agreements. With the publication of this product information, all previous editions cease to be valid. Any form of reproduction requires express prior written permission from FUCHS LUBRICANTS (UK) plc.

© FUCHS LUBRICANTS (UK) plc. All Rights reserved.