

Product Information

MOVING YOUR WORLD



SILKOLENE INJ/CARB CLEANER SPRAY

Fuel injector and carburettor cleaner.

Description

SILKOLENE INJ/CARB CLEANER SPRAY is based on a selected blend of solvents and is designed to clean fuel system components.

Application

SILKOLENE INJ/CARB CLEANER SPRAY cleans and removes lacquer, gum and resin from carburettors, fuel injection systems and automatic chokes, allowing smoother operation and improving engine efficiency. SILKOLENE INJ/CARB CLEANER SPRAY Cleaner is also suitable for cleaning throttle linkages and carburettor bodies." Directions for use: Start engine with the air filter removed. With the throttle set at quarter to half open, spray cleaner into air intake until the engine begins to stall. Cease spraying and refit the filter.

Advantages

- Suitable for all types of motorcycle fuel systems.
- Returns fuel system to original state improving performance, fuel economy rideability.
- Do not spray on a naked flame or any incandescent material and follow the safety information on the label.

Specifications

- -

Approvals

- -

FUCHS Recommendations

- -

Product Information

MOVING YOUR WORLD



TYPICAL CHARACTERISTICS

Density at 15°C	DIN 51757	0.66 g/ml
Product Dyeing		none

Product Information

MOVING YOUR WORLD



Notes

The information contained in this product information is based on the experience and know-how of FUCHS LUBRICANTS (UK) plc in the development and manufacturing of lubricants and represents the current state-of-the-art. The performance of our products can be influenced by a series of factors, especially the specific use, the method of application, the operational environment, component pre-treatment, possible external contamination, etc. For this reason, universally valid statements about the function of our products are not possible.

Our products must not be used in aircraft or spacecraft. Our products may be used in manufacture of components for aircraft or spacecraft if they are removed without residue from the components prior to assembly into the aircraft or spacecraft.

The information given in this product information represents general, non-binding guidelines. No warranty expressed or implied is given concerning the properties of the product or its suitability for any given application. We therefore recommend that you consult a FUCHS LUBRICANTS (UK) plc application engineer to discuss application conditions and the performance criteria of the products before the product is used. It is the responsibility of the user to test the functional suitability of the product and to use it with the corresponding care.

Our products undergo continuous improvement. We therefore retain the right to change our product program, the products, and their manufacturing processes as well as all details of our product information sheets at any time and without warning, unless otherwise provided in customer-specific agreements. With the publication of this product information, all previous editions cease to be valid. Any form of reproduction requires express prior written permission from FUCHS LUBRICANTS (UK) plc.

© FUCHS LUBRICANTS (UK) plc. All Rights reserved.