

# Product Information

MOVING YOUR WORLD



## SILKOLENE BRAKE/CHAIN CLEANER SPRAY

Solvent cleaner for brake systems and chains.

### Description

SILKOLENE BRAKE/CHAIN CLEANER SPRAY is a powerful solvent cleaner for cleaning and degreasing brake, chain and other metal components. SILKOLENE BRAKE/CHAIN CLEANER SPRAY is specially formulated to remove brake pad dust, prevent brake "squeal" and "chatter" and is also suitable for precision degreasing of metal parts.

### Application

SILKOLENE BRAKE/CHAIN CLEANER SPRAY can be used on all on Motorcycles, ATVs, UTVs, Karts, Cycles and other equipment with metal components. SILKOLENE BRAKE/CHAIN CLEANER SPRAY is perfect for removing unwanted deposits from chain and brake components – leaving no oily film whilst maintain chain and brake performance. Safe to use on seals and hoses. For brakes, spray directly onto affected components, allow the spray to evaporate and re-assemble. Use in a well-ventilated area. For chains, spray onto chain and allow to soak in. Agitate with a brush or a cloth and then allow to dry. Lubricate with a SILKOLENE BRAKE/CHAIN CLEANER SPRAY as soon as chain is dry. Wipe away excess.

### Advantages

- Cleans and degreases leaving no residue.
- Can be used on brakes, chains and other metal components.
- Can be used on a wide variety of machines.

### Specifications

- -

### Approvals

- -

### FUCHS Recommendations

- -

# Product Information

*MOVING YOUR WORLD*



## TYPICAL CHARACTERISTICS

---

Density at 20°C	DIN 51757	0.66 g/cm <sup>3</sup>
Product Dyeing		None

# Product Information

*MOVING YOUR WORLD*



## Notes

The information contained in this product information is based on the experience and know-how of FUCHS LUBRICANTS (UK) plc in the development and manufacturing of lubricants and represents the current state-of-the-art. The performance of our products can be influenced by a series of factors, especially the specific use, the method of application, the operational environment, component pre-treatment, possible external contamination, etc. For this reason, universally valid statements about the function of our products are not possible.

Our products must not be used in aircraft or spacecraft. Our products may be used in manufacture of components for aircraft or spacecraft if they are removed without residue from the components prior to assembly into the aircraft or spacecraft.

The information given in this product information represents general, non-binding guidelines. No warranty expressed or implied is given concerning the properties of the product or its suitability for any given application. We therefore recommend that you consult a FUCHS LUBRICANTS (UK) plc application engineer to discuss application conditions and the performance criteria of the products before the product is used. It is the responsibility of the user to test the functional suitability of the product and to use it with the corresponding care.

Our products undergo continuous improvement. We therefore retain the right to change our product program, the products, and their manufacturing processes as well as all details of our product information sheets at any time and without warning, unless otherwise provided in customer-specific agreements. With the publication of this product information, all previous editions cease to be valid. Any form of reproduction requires express prior written permission from FUCHS LUBRICANTS (UK) plc.

© FUCHS LUBRICANTS (UK) plc. All Rights reserved.