

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name: SILKOLENE INJ/CARB CLEANER SP

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses: Cleaner/degreaser

Uses advised against: No uses advised against identified.

1.3 Details of the supplier of the safety data sheet

Manufacturer / Supplier FUCHS LUBRICANTS (UK) PLC.
New Century Street
ST1 5HU Hanley

Telephone: +44 (0) 1782 203700

Contact Person: Product Safety department

E-mail: product.safety@fuchs.com
Telephone: +44 (0) 1782 203700

1.4 Emergency telephone number: UK NHS: Dial 111

SECTION 2: Hazards identification

Product name: SILKOLENE INJ/CARB CLEANER SP

2.1 Classification of the substance or mixture

The product has been classified and labelled as hazardous according to regulation GB-CLP.

Classification according to GB-CLP.

Physical Hazards

Aerosols	Category 1	H222: Extremely flammable aerosol. H229: Pressurized container: May burst if heated.
----------	------------	-----------------------------------------------------------------------------------------

Health Hazards

Skin irritation	Category 2	H315: Causes skin irritation.
Serious eye irritation	Category 2	H319: Causes serious eye irritation.
Specific Target Organ Toxicity - Single Exposure	Category 3	H336: May cause drowsiness or dizziness.
Aspiration Hazard	Category 1	H304: May be fatal if swallowed and enters airways.

Environmental Hazards

Chronic hazards to the aquatic environment	Category 3	H412: Harmful to aquatic life with long lasting effects.
--------------------------------------------	------------	----------------------------------------------------------

Hazard summary

Physical Hazards: Flammable aerosol.

Health Hazards

Inhalation: Has a narcotic effect.

Ingestion: If ingested, material may be aspirated into the lungs and cause chemical pneumonitis. Treat appropriately.

2.2 Label Elements

Contains: Acetone
Hydrocarbons, low viscous



Signal Words: Danger

Hazard Statement(s): H222: Extremely flammable aerosol.
H229: Pressurized container: May burst if heated.
H315: Causes skin irritation.
H319: Causes serious eye irritation.
H336: May cause drowsiness or dizziness.
H412: Harmful to aquatic life with long lasting effects.

Product name: SILKOLENE INJ/CARB CLEANER SP

Precautionary Statements

Prevention:	<p>P102: Keep out of reach of children. P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211: Do not spray on an open flame or other ignition source. P251: Do not pierce or burn, even after use. P261: Avoid breathing dust/fume/gas/mist/vapors/spray. P262: Do not get in eyes, on skin, or on clothing. P273: Avoid release to the environment.</p>
Storage:	P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F.
Disposal:	P501: Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Supplemental label information

EUH066: Repeated exposure may cause skin dryness or cracking.

2.3 Other hazards:	By handling of mineral oil products and chemical products no particular hazard is known when normal precautions (item 7) and personal protective equipment (item 8) are kept. The product may not be released into the environment without control.
---------------------------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

SECTION 3: Composition/information on ingredients

3.2 Mixtures

General information: Mixture of components with propellant in aerosol can.

Chemical name	Identifier	Concentration *	UK-REACH Registration No.	Notes
Butane	EINECS: 203-448-7	0% - <100,00%		
Propane	EINECS: 200-827-9	0% - <100,00%		
Isobutane (<0,1% 1,3-butadiene)	EINECS: 200-857-2	0% - <100,00%		
Acetone	EINECS: 200-662-2	20,00% - <50,00%		
Xylene	EINECS: 215-535-7	10,00% - <20,00%		
Hydrocarbons, low viscous	EC: 921-024-6	10,00% - <20,00%		
Benzene derivative	EINECS: 202-849-4	1,00% - <5,00%		

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

PBT: persistent, bioaccumulative and toxic substance.

vPvB: very persistent and very bioaccumulative substance.

Product name: SILKOLENE INJ/CARB CLEANER SP

Classification

Chemical name	Identifier	Classification
Butane	EINECS: 203-448-7	GBCLP: Flam. Gas 1A;H220, Press. Gas Compr. Gas;H280
Propane	EINECS: 200-827-9	GBCLP: Flam. Gas 1A;H220, Press. Gas Compr. Gas;H280
Isobutane (<0,1% 1,3-butadiene)	EINECS: 200-857-2	GBCLP: Flam. Gas 1A;H220, Press. Gas Compr. Gas;H280
Acetone	EINECS: 200-662-2	GBCLP: Flam. Liq. 2;H225, Eye Irrit. 2;H319, STOT SE 3;H336 EUH066
Xylene	EINECS: 215-535-7	GBCLP: Flam. Liq. 3;H226, Acute Tox. 4;H312, Acute Tox. 4;H332, Skin Irrit. 2;H315
Hydrocarbons, low viscous	EC: 921-024-6	GBCLP: Flam. Liq. 2;H225, Asp. Tox. 1;H304, Skin Irrit. 2;H315, STOT SE 3;H336, Aquatic Chronic 2;H411
Benzene derivative	EINECS: 202-849-4	GBCLP: Flam. Liq. 2;H225, Acute Tox. 4;H332

GB-CLP

SECTION 4: First aid measures

General: Instantly remove any clothing soiled by the product.

4.1 Description of first aid measures

Inhalation: Supply fresh air; consult doctor in case of symptoms.

Eye contact: Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. Get medical attention.

Skin Contact: Immediately flush with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash contaminated clothing before reuse. Get medical attention.

Ingestion: Call a physician or poison control center immediately. Rinse mouth. Never give liquid to an unconscious person. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Do NOT induce vomiting. Call a POISON CENTER or doctor/ physician if you feel unwell.

4.2 Most important symptoms and effects, both acute and delayed: Causes serious eye irritation. Causes skin irritation. If ingested, material may be aspirated into the lungs and cause chemical pneumonitis. Treat appropriately. Dizziness Freeze burns

4.3 Indication of any immediate medical attention and special treatment needed Get medical attention if symptoms occur.

SECTION 5: Firefighting measures

General Fire Hazards: Use water spray to keep fire-exposed containers cool. Fight fire from a protected location. Move containers from fire area if you can do so without risk.

Product name: SILKOLENE INJ/CARB CLEANER SP

5.1 Extinguishing media

Suitable extinguishing media: CO₂, fire extinguishing powder or fog like water spraying. Extinguish larger fires with alcohol resistant foam or spray water with suitable surfactant added

Unsuitable extinguishing media: Water with a full water jet.

5.2 Special hazards arising from the substance or mixture: Danger of explosion with aerosol cans.

5.3 Advice for firefighters

Special fire-fighting procedures: Move container from fire area if it can be done without risk. Dispose of fire debris and contaminated fire fighting water in accordance with official regulations. Collect contaminated fire fighting water separately. It must not enter drains.

Special protective equipment for fire-fighters: Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures: Ventilate closed spaces before entering them. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep upwind. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep unauthorized personnel away.

6.2 Environmental Precautions: Avoid release to the environment. Prevent further leakage or spillage if safe to do so.

6.3 Methods and material for containment and cleaning up: Scrape up spillage or absorb with absorbing material. Stop the flow of material, if this is without risk. Dispose of the material collected according to regulations.

6.4 Reference to other sections: See Section 8 of the SDS for Personal Protective Equipment. See Section 7 for information on safe handling See Section 13 for information on disposal.

Dike for later disposal. Prevent entry into waterways, sewer, basements or confined areas. Stop the flow of material, if this is without risk. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop leak if you can do so without risk.

Product name: SILKOLENE INJ/CARB CLEANER SP

SECTION 7: Handling and storage:

7.1 Precautions for safe handling: Avoid contact with eyes. Wash hands thoroughly after handling. Do not eat, drink or smoke when working with the product. Take usual precautions when handling mineral oil products or chemical products. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid contact with skin. Avoid contact with flame and heat source, prevent contact with direct sunlight Use only in well-ventilated areas.

7.2 Conditions for safe storage, including any incompatibilities: Store locked up. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Local regulations concerning handling and storage of waterpolluting products have to be followed. Local regulations for the storage and handling of aerosol cans and flammable liquids have to be kept. Keep away from heat/sparks/hot surfaces. - No smoking.

7.3 Specific end use(s): Not applicable

Storage Class: 2 B, Aerosols

SECTION 8: Exposure controls/personal protection

8.1 Control Parameters

Occupational Exposure Limits

Chemical name	Type	Exposure Limit Values	Source
Butane	TWA	600 ppm 1.450 mg/m3	UK. EH40 Workplace Exposure Limits (WELs), as amended (12 2011)
Butane	STEL	750 ppm 1.810 mg/m3	UK. EH40 Workplace Exposure Limits (WELs), as amended (12 2011)
Acetone	TWA	500 ppm 1.210 mg/m3	UK. EH40 Workplace Exposure Limits (WELs), as amended (12 2011)
Acetone	STEL	1.500 ppm 3.620 mg/m3	UK. EH40 Workplace Exposure Limits (WELs), as amended (12 2011)
Benzene derivative	TWA	100 ppm 441 mg/m3	UK. EH40 Workplace Exposure Limits (WELs), as amended (12 2011)
Benzene derivative	STEL	125 ppm 552 mg/m3	UK. EH40 Workplace Exposure Limits (WELs), as amended (12 2011)

8.2 Exposure controls

Appropriate engineering controls: Provide adequate ventilation. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Product name: SILKOLENE INJ/CARB CLEANER SP

General information:	Wash hands before breaks and after work. Use personal protective equipment as required. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment. The usual precautionary measures should be adhered to in handling the chemicals or the mineral oil products.
Eye/face protection:	Safety glasses (EN 166) recommended during refilling. Avoid contact with eyes.
Skin protection	
Hand Protection:	Material: Nitrile butyl rubber (NBR). Min. Breakthrough time: >= 480 min Recommended thickness of the material: >= 0,38 mm Avoid long-term and repeated skin contact. Suitable gloves can be recommended by the glove supplier. Use skin protection cream for preventive skin protection. Protective gloves, where permitted in acc. to safety directions. The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
Other:	Do not carry cleaning cloths impregnated with the product in trouser pockets. Wear suitable protective clothing.
Respiratory Protection:	Ensure good ventilation/exhaustion at the workplace. Avoid breathing vapour/ aerosol.
Thermal hazards:	Not known.
Hygiene measures:	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing to remove contaminants. Discard contaminated footwear that cannot be cleaned.
Environmental Controls:	No data available.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state:	Aerosols
Form:	Aerosols
Color:	Colorless
Odor:	Characteristic
pH:	substance/mixture is non-soluble (in water)
Freezing point:	not determined
Boiling Point:	not determined
Flash Point:	Value not relevant for classification
Evaporation Rate:	Not applicable for mixtures
Flammability (solid, gas):	not determined
Flammability Limit - Upper (%)–:	Not applicable for mixtures

Product name: SILKOLENE INJ/CARB CLEANER SP

Flammability Limit - Lower (%)–:	Not applicable for mixtures
Vapor pressure:	Not applicable for mixtures
Relative vapor density:	Not applicable for mixtures
Density:	0,66 g/cm ³ (15 °C)
Solubility(ies)	
Solubility in Water:	Insoluble in water
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	Not applicable for mixtures
Autoignition Temperature:	not determined
Decomposition Temperature:	not determined
Flow time	Value not relevant for classification
Explosive properties:	Value not relevant for classification
Oxidizing properties:	Value not relevant for classification
Particle characteristics:	Not applicable
9.2 Other information	No data available.

SECTION 10: Stability and reactivity

10.1 Reactivity:	Stable under normal use conditions.
10.2 Chemical Stability:	Stable under normal use conditions.
10.3 Possibility of hazardous reactions:	Stable under normal use conditions.
10.4 Conditions to avoid:	Stable under normal use conditions.
10.5 Incompatible Materials:	Strong oxidizing substances. Strong acids. Strong bases.
10.6 Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

SECTION 11: Toxicological information

Information on likely routes of exposure

Inhalation:	No data available.
Ingestion:	No data available.
Skin Contact:	Causes skin irritation.
Eye contact:	Causes eye irritation.

11.1 Information on toxicological effects

Acute toxicity

Oral

Product:	Not classified for acute toxicity based on available data.
-----------------	------------------------------------------------------------

Product name: SILKOLENE INJ/CARB CLEANER SP

Specified substance(s)

Acetone	LD 50 (Rat): 5.800 mg/kg (OECD 401)
Xylene	LD 50 (Rat): 8.700 mg/kg
Benzene derivative	LD 50 (Rat): 3.500 mg/kg

Dermal

Product: ATEmix: 11.862 mg/kg

Specified substance(s)

Acetone	LD 50 (Rabbit): > 15.800 mg/kg
Xylene	LD 50 (Rabbit): 2.000 mg/kg
Benzene derivative	LD 50 (Rabbit): 17.800 mg/kg

Inhalation

Product: ATEmix: 55,47 mg/l
Vapour Vapour

Specified substance(s)

Butane	LC 50 (Rat, 4 h): 658 mg/l Gas
Acetone	LC 50 (Rat, 4 h): 76 mg/l
Xylene	LC 50 (Rat, 4 h): 6.350 mg/l Vapour

Skin Corrosion/Irritation:

Product: Based on available data, the classification criteria are met.

Specified substance(s)

Acetone
Prolonged skin contact may cause redness, irritation and dry skin.

Serious Eye Damage/Eye Irritation:

Product: Based on available data, the classification criteria are met.

Specified substance(s)

Acetone
OECD 405 (Rabbit):
Causes serious eye irritation.

Respiratory or Skin Sensitization:

Product: Skin sensitizer: Based on available data, the classification criteria are not met.

Respiratory sensitizer: Based on available data, the classification criteria are not met.

Specified substance(s)

Acetone
Based on available data, the classification criteria are not met.

Product name: SILKOLENE INJ/CARB CLEANER SP

Germ Cell Mutagenicity

Product: Based on available data, the classification criteria are not met.

In vitro

Specified substance(s)

Acetone

Based on available data, the classification criteria are not met.

In vivo

Specified substance(s)

Acetone

Based on available data, the classification criteria are not met.

Carcinogenicity

Product:

Based on available data, the classification criteria are not met.

Specified substance(s)

Acetone

Based on available data, the classification criteria are not met.

Reproductive toxicity

Product:

Based on available data, the classification criteria are not met.

Specified substance(s)

Acetone

Based on available data, the classification criteria are not met.

Specific Target Organ Toxicity - Single Exposure

Product:

Based on available data, the classification criteria are met.

Specified substance(s)

Acetone

May cause drowsiness or dizziness.

Specific Target Organ Toxicity - Repeated Exposure

Product:

Based on available data, the classification criteria are not met.

Specified substance(s)

Acetone

Based on available data, the classification criteria are not met.

Aspiration Hazard

Product:

May be fatal if swallowed and enters airways.

Other adverse effects:

No data available.

SECTION 12: Ecological information

12.1 Toxicity

Acute toxicity

Product:

Based on available data, the classification criteria are not met.

Fish

Specified substance(s)

Propane

LC 50 (Fish, 96 h): > 1.000 mg/l

Isobutane (<0,1% 1,3-butadiene)

LC 50 (Fish, 96 h): 28 mg/l

Product name: SILKOLENE INJ/CARB CLEANER SP

Acetone	LC 50 (Fish, 96 h): 5.540 mg/l
Hydrocarbons, low vis- cous	LC 50 (Fish, 96 h): 11,4 mg/l (OECD 203)
Aquatic Invertebrates	
Specified substance(s)	
Isobutane (<0,1% 1,3- butadiene)	EC 50 (Water Flea, 48 h): 16,3 mg/l
Acetone	EC 50 (Water Flea, 48 h): 8.800 mg/l
Hydrocarbons, low vis- cous	LC 50 (Water Flea, 48 h): 3 mg/l (OECD 202)

Chronic Toxicity

Product: Based on available data, the classification criteria are met.

Toxicity to Aquatic Plants

Specified substance(s)
Isobutane (<0,1% 1,3-
butadiene) EC 50 (Alga, 72 h): 8,6 mg/l

Hydrocarbons, low vis-
cous LC 50 (Alga, 72 h): 30 mg/l (OECD 201)

12.2 Persistence and Degradability

Biodegradation

Product: Not applicable for mixtures
Specified substance(s)
Acetone The product is easily biodegradable.

12.3 Bioaccumulative potential

Product: Not applicable for mixtures
Specified substance(s)
Acetone Bioconcentration Factor (BCF): 0,69 The product is not bioaccumulating.

12.4 Mobility in soil:

Product: Not applicable for mixtures

**12.5 Results of PBT and vPvB
assessment:**

The product does not contain any substances fulfilling the PBT/vPvB criteria.

12.6 Other adverse effects:

Harmful to aquatic life with long lasting effects.

**Water Hazard Class
(WGK):**

WGK 2: significantly water-endangering.

Product name: SILKOLENE INJ/CARB CLEANER SP

SECTION 13: Disposal considerations

13.1 Waste treatment methods

General information: Dispose in accordance with all applicable regulations.

Disposal methods: Discharge, treatment, or disposal may be subject to national, state, or local laws.

List of Waste (LoW) Codes

16 05 04*: Gases in pressure containers (including halons) containing hazardous substances.

SECTION 14: Transport information

ADR/RID

14.1 UN number or ID number: UN 1950
14.2 UN Proper Shipping Name: AEROSOLS
14.3 Transport Hazard Class(es)
Class: 2
Label(s): 2.1
Hazard No. (ADR): –
Tunnel restriction code: (D)
14.4 Packing Group: –
14.5 Environmental hazards: –
14.6 Special precautions for user: –

IMDG

14.1 UN number or ID number: UN 1950
14.2 UN Proper Shipping Name: AEROSOLS
14.3 Transport Hazard Class(es)
Class: 2.1
Label(s): 2.1
EmS No.: F-D, S-U
14.3 Packing Group: –
14.5 Environmental hazards: –
14.6 Special precautions for user: –

IATA

14.1 UN number or ID number: UN 1950
14.2 Proper Shipping Name: Aerosols, flammable
14.3 Transport Hazard Class(es):
Class: 2.1
Label(s): 2.1
14.4 Packing Group: –
14.5 Environmental hazards: –
14.6 Special precautions for user: –

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code: Not applicable.

Product name: SILKOLENE INJ/CARB CLEANER SP

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

GB Regulations

The Ozone-Depleting Substances and Fluorinated Greenhouse Gases (Amendment etc.) (EU Exit) Regulations 2019:

none

The Persistent Organic Pollutants (Amendment) (EU Exit) Regulations 2020:

none

15.2 Chemical safety assessment:

No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

Revision Information:

Vertical lines in the margin indicate an amendment.

Wording of the H-statements in section 2 and 3

EUH066	Repeated exposure may cause skin dryness or cracking.
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapor.
H226	Flammable liquid and vapor.
H229	Pressurized container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Other information:

The classification complies with the current GB lists; however, it has been supplemented with expert literature information and information provided by/about our company. The following evaluation methods were used: On the basis of test data; Calculation Method; Bridging Principle "Substantially similar mixtures"; Expert Judgement

Revision Date:

11.01.2023

Product name: SILKOLENE INJ/CARB CLEANER SP

Disclaimer:

The data contained in this safety data sheet are based on our current knowledge and experience and are given to the best of our knowledge and belief. It characterizes the product only with regard to safety requirements for handling, transport and disposal. The data do not describe the product's properties (tech. product specification). Neither should any agreed property nor the suitability of the product for any specific technical application be deduced from the data contained in this safety data sheet. Modifications on this document are not allowed. The data are not transferable to other products. In the case of mixing the product with other products or in the case of processing, the data in this safety data sheet are not necessarily valid for the new-made material. It is the responsibility of the recipient of the product to observe federal, state and local law. Please contact us to obtain up-to-date safety data sheets. This document was issued electronically and has no signature.