

Product Information

MOVING YOUR WORLD



SILKOLENE PRO BOOST

Power Boost fuel additive

Description

SILKOLENE PRO BOOST is a synthetic low-toxicity organic chemical creating a highly efficient power improver specifically designed to combat pre-ignition - often called 'pinking' or 'knocking'. This in turn leads to improved acceleration. SILKOLENE PRO BOOST burns cleanly without leaving deposits in the combustion chamber. Adding SILKOLENE PRO BOOST to petrol will have a 'keep clean effect' in both carburetor and injector fuel systems and will also help to reduce icing in carburetors. SILKOLENE PRO BOOST also reduces fuel system corrosion.

Application

SILKOLENE PRO BOOST has been successfully tested in a wide variety of car and motorcycle engines, including 2-stroke. It is suitable for all petrol engines and all qualities of fuel. SILKOLENE PRO BOOST does not affect mixture settings making carburetor adjustment unnecessary. It is fully compatible with all petrol fuels and does not attack fuel hoses or filters.

Advantages

- SILKOLENE PRO BOOST can be used between 1% and 3%.
- Accidental overdosing will have no adverse effects.
- Highly efficient power booster.
- Improves acceleration by combating pre-ignition.
- Compatible with catalytic converters.
- Keeps fuel system and combustion chamber clean and deposit free.
- Does not contain lead or aniline.
- Promotes more complete combustion helping reduce harmful exhaust gases such as carbon monoxide.

Specifications

- -

Approvals

- -

FUCHS Recommendations

- -

Product Information

MOVING YOUR WORLD



TYPICAL CHARACTERISTICS

Density at 20°C	DIN 51757	g/ml
Closed Flash Point	ASTM D93	-28 °C
Product Dyeing		none

Product Information

MOVING YOUR WORLD



Notes

The information contained in this product information is based on the experience and know-how of FUCHS LUBRICANTS (UK) plc in the development and manufacturing of lubricants and represents the current state-of-the-art. The performance of our products can be influenced by a series of factors, especially the specific use, the method of application, the operational environment, component pre-treatment, possible external contamination, etc. For this reason, universally valid statements about the function of our products are not possible.

Our products must not be used in aircraft or spacecraft. Our products may be used in manufacture of components for aircraft or spacecraft if they are removed without residue from the components prior to assembly into the aircraft or spacecraft.

The information given in this product information represents general, non-binding guidelines. No warranty expressed or implied is given concerning the properties of the product or its suitability for any given application. We therefore recommend that you consult a FUCHS LUBRICANTS (UK) plc application engineer to discuss application conditions and the performance criteria of the products before the product is used. It is the responsibility of the user to test the functional suitability of the product and to use it with the corresponding care.

Our products undergo continuous improvement. We therefore retain the right to change our product program, the products, and their manufacturing processes as well as all details of our product information sheets at any time and without warning, unless otherwise provided in customer-specific agreements. With the publication of this product information, all previous editions cease to be valid. Any form of reproduction requires express prior written permission from FUCHS LUBRICANTS (UK) plc.

© FUCHS LUBRICANTS (UK) plc. All Rights reserved.