

Product Information

MOVING YOUR WORLD



SILKOLENE SILKOPEN SPRAY

Graphited maintenance spray.

Description

SILKOLENE SILKOPEN SPRAY is a graphited penetrating spray which helps release seized thread fasteners. SILKOLENE SILKOPEN SPRAY contains a suspension of very fine graphite dispersed in a light, searching carrier fluid. NOTE: May affect certain rubbers and plastics.

Application

SILKOLENE SILKOPEN SPRAY penetrates and helps release seized thread fasteners. SILKOLENE SILKOPEN SPRAY can also be used to lubricate and clean brake and clutch cables and when used with a cable oiler and penetrates the full length of the cable, forcing out dirt and corrosion, leaving a thin graphite and oil lubricating film for a silky smooth lever action. SILKOLENE SILKOPEN SPRAY can also be used for general lubrication and will provide short term corrosion protection. Shake can well before application. Ensure location is well ventilated. Spray liberally onto rusted components. Allow to soak in. Tap, rotate or vibrate components to help loosen them. Repeat process until parts are free.

Advantages

- Lubricates and penetrates.
- Helps release seized nuts and bolts.
- Short term corrosion protection.
- Helps free up and lubricate brake and clutch cables.
- Do not spray on a naked flame or any incandescent material and follow the safety information on the label.

Specifications

- -

Approvals

- -

FUCHS Recommendations

- -

Product Information

MOVING YOUR WORLD



TYPICAL CHARACTERISTICS

Density at 15°C	DIN 51757	0.72 g/ml
Product Dyeing		Black

Product Information

MOVING YOUR WORLD



Notes

The information contained in this product information is based on the experience and know-how of FUCHS LUBRICANTS (UK) plc in the development and manufacturing of lubricants and represents the current state-of-the-art. The performance of our products can be influenced by a series of factors, especially the specific use, the method of application, the operational environment, component pre-treatment, possible external contamination, etc. For this reason, universally valid statements about the function of our products are not possible.

Our products must not be used in aircraft or spacecraft. Our products may be used in manufacture of components for aircraft or spacecraft if they are removed without residue from the components prior to assembly into the aircraft or spacecraft.

The information given in this product information represents general, non-binding guidelines. No warranty expressed or implied is given concerning the properties of the product or its suitability for any given application. We therefore recommend that you consult a FUCHS LUBRICANTS (UK) plc application engineer to discuss application conditions and the performance criteria of the products before the product is used. It is the responsibility of the user to test the functional suitability of the product and to use it with the corresponding care.

Our products undergo continuous improvement. We therefore retain the right to change our product program, the products, and their manufacturing processes as well as all details of our product information sheets at any time and without warning, unless otherwise provided in customer-specific agreements. With the publication of this product information, all previous editions cease to be valid. Any form of reproduction requires express prior written permission from FUCHS LUBRICANTS (UK) plc.

© FUCHS LUBRICANTS (UK) plc. All Rights reserved.