

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name: SILKOLENE RSF 2.5

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses: Hydraulic fluid Anticorrosion product Cleaning agent/ Cleaner Containers $\geq 20l$ for commercial use only

Uses advised against: No uses advised against identified. No uses advised against identified.

1.3 Details of the supplier of the safety data sheet

Manufacturer / Supplier FUCHS LUBRICANTS (UK) PLC.
New Century Street
ST1 5HU Hanley

Telephone: +44 (0) 1782 203700

Contact Person: Product Safety department

E-mail: product.safety@fuchs.com
Telephone: +44 (0) 1782 203700

1.4 Emergency telephone number: UK NHS: Dial 111

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

The product has been classified and labelled as hazardous according to regulation GB-CLP.

Classification according to GB-CLP.

Health Hazards

Aspiration Hazard Category 1 H304: May be fatal if swallowed and enters airways.

Hazard summary

Physical Hazards: Can form flammable vapour-air mixtures during the application.

Health Hazards

Ingestion: If ingested, material may be aspirated into the lungs and cause chemical pneumonitis. Treat appropriately.

2.2 Label Elements

Product name: SILKOLENE RSF 2.5

Contains: Base oil, low viscous
Hydrocarbons, low viscosity



Signal Words: Danger

Hazard Statement(s): H304: May be fatal if swallowed and enters airways.

Precautionary Statements

Response: P301+P310: IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P331: Do NOT induce vomiting.

Supplemental label information

EUH066: Repeated exposure may cause skin dryness or cracking.

2.3 Other hazards: By handling of mineral oil products and chemical products no particular hazard is known when normal precautions (item 7) and personal protective equipment (item 8) are kept. The product may not be released into the environment without control.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

General information: Mixture based on severely refined mineral base oils with corrosion preventive agents and volatile hydrocarbons.

Chemical name	Identifier	Concentration *	UK-REACH Registration No.	Notes
Base oil, low viscous	EINECS: 232-455-8	50,00% - <100,00%		
Hydrocarbons, low viscosity	EINECS: 926-141-6	20,00% - <50,00%		
Toluene	EINECS: 203-625-9	0,10% - <1,00%		

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.
PBT: persistent, bioaccumulative and toxic substance.
vPvB: very persistent and very bioaccumulative substance.

Product name: SILKOLENE RSF 2.5

Classification

Chemical name	Identifier	Classification
Base oil, low viscous	EINECS: 232-455-8	GBCLP: Asp. Tox. 1;H304
Hydrocarbons, low viscosity	EINECS: 926-141-6	GBCLP: Asp. Tox. 1;H304 EUH066
Toluene	EINECS: 203-625-9	GBCLP: Flam. Liq. 2;H225, Asp. Tox. 1;H304, Repr. 2;H361d, STOT RE 2;H373, Skin Irrit. 2;H315, STOT SE 3;H336

GB-CLP

Please note that the mineral oils and petroleum distillates used in our products are severely refined and have a DMSO extract < 3% as measured by method IP 346 and are not classified as carcinogenic according to Note L of Annex VI of Regulation GB-CLP.

SECTION 4: First aid measures

General: Instantly remove any clothing soiled by the product.

4.1 Description of first aid measures

Inhalation: Supply fresh air; consult doctor in case of symptoms.

Eye contact: Promptly wash eyes with plenty of water while lifting the eye lids.

Skin Contact: Wash with water and soap; pay attention: skin degreasing product.

Ingestion: Call a physician or poison control center immediately. Rinse mouth. Never give liquid to an unconscious person. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed: If ingested, material may be aspirated into the lungs and cause chemical pneumonitis. Treat appropriately. Headache.

4.3 Indication of any immediate medical attention and special treatment needed: Get medical attention if symptoms occur.

SECTION 5: Firefighting measures

General Fire Hazards: Use water spray to keep fire-exposed containers cool.

5.1 Extinguishing media

Suitable extinguishing media: CO₂, fire extinguishing powder or fog like water spraying. Extinguish larger fires with alcohol resistant foam or spray water with suitable surfactant added

Unsuitable extinguishing media: Water with a full water jet.

Product name: SILKOLENE RSF 2.5

5.2 Special hazards arising from the substance or mixture:	Can form explosive vapor-air mixtures at higher temperatures.
5.3 Advice for firefighters	
Special fire-fighting procedures:	Move container from fire area if it can be done without risk. Dispose of fire debris and contaminated fire fighting water in accordance with official regulations. Collect contaminated fire fighting water separately. It must not enter drains.
Special protective equipment for fire-fighters:	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures:	In case of spills, beware of slippery floors and surfaces. Keep away from sources of ignition - No smoking.
6.2 Environmental Precautions:	Prevent from spreading (e.g. by binding or oil barriers). Avoid release to the environment. Environmental manager must be informed of all major spillages. Prevent further leakage or spillage if safe to do so. Do not allow to enter drainage system, surface or ground water.
6.3 Methods and material for containment and cleaning up:	Absorb with liquid-binding material (sand, diatomite, acidbinders, universal binders, sawdust). Dispose of the material collected according to regulations. Stop the flow of material, if this is without risk.
6.4 Reference to other sections:	See Section 8 of the SDS for Personal Protective Equipment. See Section 7 for information on safe handling See Section 13 for information on disposal.

SECTION 7: Handling and storage:

7.1 Precautions for safe handling:	Use only in well-ventilated areas. Risk of vapor concentration on the floor and in low-lying areas. Prevent formation of aerosols. Do not eat, drink or smoke when working with the product. Take usual precautions when handling mineral oil products or chemical products. Observe good industrial hygiene practices. Provide adequate ventilation.
7.2 Conditions for safe storage, including any incompatibilities:	Store locked up. Local regulations concerning handling and storage of waterpolluting products have to be followed. The precautions for storing and handling of flammable liquids have to be kept. Local regulations for common storage of flammable liquids have to be followed. Do not heat up to temperatures close to the flash point.
7.3 Specific end use(s):	Not applicable
Storage Class:	10, Combustible liquids

Product name: SILKOLENE RSF 2.5

SECTION 8: Exposure controls/personal protection

8.1 Control Parameters

Occupational Exposure Limits

Chemical name	Type	Exposure Limit Values	Source
Toluene	TWA	50 ppm 191 mg/m3	UK. EH40 Workplace Exposure Limits (WELs), as amended (12 2011)
Toluene	STEL	100 ppm 384 mg/m3	UK. EH40 Workplace Exposure Limits (WELs), as amended (12 2011)

8.2 Exposure controls

Appropriate engineering controls:

Provide adequate ventilation. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

General information:

Wash hands before breaks and after work. Use personal protective equipment as required. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment. The usual precautionary measures should be adhered to in handling the chemicals or the mineral oil products.

Eye/face protection:

Safety glasses (EN 166) recommended during refilling.

Skin protection

Hand Protection:

Material: Nitrile butyl rubber (NBR).
Min. Breakthrough time: >= 480 min
Recommended thickness of the material: >= 0,38 mm

Avoid long-term and repeated skin contact. Suitable gloves can be recommended by the glove supplier. Use skin protection cream for preventive skin protection. Protective gloves, where permitted in acc. to safety directions. The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Other:

Do not carry cleaning cloths impregnated with the product in trouser pockets. Wear suitable protective clothing.

Respiratory Protection:

Ensure good ventilation/exhaustion at the workplace. Avoid breathing vapour/ aerosol.

Thermal hazards:

Not known.

Hygiene measures:

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing to remove contaminants. Discard contaminated footwear that cannot be cleaned.

Product name: SILKOLENE RSF 2.5

Environmental Controls: No data available.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state:	liquid
Form:	liquid
Color:	Yellow
Odor:	Characteristic
pH:	substance/mixture is non-soluble (in water)
Freezing point:	not determined
Boiling Point:	175 °C
Flash Point:	75 °C
Evaporation Rate:	Not applicable for mixtures
Flammability (solid, gas):	not determined
Flammability Limit - Upper (%)-:	Not applicable for mixtures
Flammability Limit - Lower (%)-:	Not applicable for mixtures
Vapor pressure:	Not applicable for mixtures
Relative vapor density:	Not applicable for mixtures
Density:	0,81 g/cm ³ (15 °C)
Solubility(ies)	
Solubility in Water:	Insoluble in water
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	Not applicable for mixtures
Autoignition Temperature:	not determined
Decomposition Temperature:	not determined
Kinematic viscosity:	14 mm ² /s (40 °C)
Explosive properties:	Value not relevant for classification
Oxidizing properties:	Value not relevant for classification
Particle characteristics:	Not applicable

9.2 Other information No data available.

SECTION 10: Stability and reactivity

10.1 Reactivity:	Stable under normal use conditions.
10.2 Chemical Stability:	Stable under normal use conditions.
10.3 Possibility of hazardous reactions:	Stable under normal use conditions.
10.4 Conditions to avoid:	Stable under normal use conditions.
10.5 Incompatible Materials:	Strong oxidizing substances. Strong acids. Strong bases.

Product name: SILKOLENE RSF 2.5

10.6 Hazardous Decomposition Products: Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Oral

Product: Not classified for acute toxicity based on available data.

Specified substance(s)

Base oil, low viscous LD 50 (Rat): > 5.001 mg/kg (OECD 401)

Hydrocarbons, low viscosity LD 50 (Rat): > 5.000 mg/kg (OECD 401)

Dermal

Product: Not classified for acute toxicity based on available data.

Specified substance(s)

Hydrocarbons, low viscosity LD 50 (Rabbit): > 5.000 mg/kg (OECD 402)

Toluene LD 50 (Rabbit): 12.124 mg/kg

Inhalation

Product: Not classified for acute toxicity based on available data.

Skin Corrosion/Irritation:

Product: Based on available data, the classification criteria are not met.

Specified substance(s)

Base oil, low viscous OECD 404 (Rabbit):
Not irritant.

Hydrocarbons, low viscosity OECD 404
Not irritant.

Serious Eye Damage/Eye Irritation:

Product: Based on available data, the classification criteria are not met.

Specified substance(s)

Base oil, low viscous OECD 405 (Rabbit):
Not irritant.

Product name: SILKOLENE RSF 2.5

Respiratory or Skin Sensitization:

Product: Skin sensitizer: Based on available data, the classification criteria are not met.
Respiratory sensitizer: Based on available data, the classification criteria are not met.

Specified substance(s)

Base oil, low viscous
No sensitizing effect (guinea pig); OECD 406

Hydrocarbons, low viscosity
No sensitizing effect (guinea pig); OECD 406

Germ Cell Mutagenicity

Product: Based on available data, the classification criteria are not met.

Carcinogenicity

Product: Based on available data, the classification criteria are not met.

Reproductive toxicity

Product: Based on available data, the classification criteria are not met.

Specific Target Organ Toxicity - Single Exposure

Product: Based on available data, the classification criteria are not met.

Specific Target Organ Toxicity - Repeated Exposure

Product: Based on available data, the classification criteria are not met.

Aspiration Hazard

Product: May be fatal if swallowed and enters airways.

Other adverse effects: No data available.

SECTION 12: Ecological information

General information: Not applicable

12.1 Toxicity

Acute toxicity

Product: Based on available data, the classification criteria are not met.

Fish

Specified substance(s)
Base oil, low viscous
LC 50 (Fish, 96 h): > 1.001 mg/l (OECD 203)

Hydrocarbons, low viscosity
LC 50 (Fish, 96 h): 1.000 mg/l (OECD 203)

Aquatic Invertebrates

Specified substance(s)
Base oil, low viscous
EC 50 (Water Flea, 48 h): > 101 mg/l (OECD 202)

Product name: SILKOLENE RSF 2.5

Hydrocarbons, low viscosity LC 50 (Water Flea, 48 h): > 1.000 mg/l (OECD 202)

Chronic Toxicity

Product: Based on available data, the classification criteria are not met.

Toxicity to Aquatic Plants

Specified substance(s)

Base oil, low viscous EC 50 (Alga, 72 h): > 1.001 mg/l

Hydrocarbons, low viscosity EC 50 (Alga, 72 h): > 1.000 mg/l (OECD 201)

12.2 Persistence and Degradability

Biodegradation

Product: Not applicable for mixtures

Specified substance(s)

Hydrocarbons, low viscosity 69 % (28 d, OECD 301F) Readily biodegradable

12.3 Bioaccumulative potential

Product: Not applicable for mixtures

12.4 Mobility in soil:

Product: Not applicable for mixtures

12.5 Results of PBT and vPvB assessment:

The product does not contain any substances fulfilling the PBT/vPvB criteria.

12.6 Other adverse effects:

No data available.

Water Hazard Class (WGK):

WGK 1: slightly water-endangering.

SECTION 13: Disposal considerations
--

13.1 Waste treatment methods

General information: Dispose in accordance with all applicable regulations.

Disposal methods: Discharge, treatment, or disposal may be subject to national, state, or local laws.

List of Waste (LoW) Codes

13 02 05*: mineral-based non-chlorinated engine, gear and lubricating oils

Product name: SILKOLENE RSF 2.5

SECTION 14: Transport information

ADR/RID

- 14.1 UN number or ID number: –
- 14.2 UN Proper Shipping Name: –
- 14.3 Transport Hazard Class(es)
 - Class: Non-dangerous goods
 - Label(s): –
 - Hazard No. (ADR): –
 - Tunnel restriction code: –
- 14.4 Packing Group: –
- 14.5 Environmental hazards: –
- 14.6 Special precautions for user: –

IMDG

- 14.1 UN number or ID number: –
- 14.2 UN Proper Shipping Name: –
- 14.3 Transport Hazard Class(es)
 - Class: Non-dangerous goods
 - Label(s): –
 - EmS No.: –
- 14.3 Packing Group: –
- 14.5 Environmental hazards: –
- 14.6 Special precautions for user: –

IATA

- 14.1 UN number or ID number: –
- 14.2 Proper Shipping Name: –
- 14.3 Transport Hazard Class(es):
 - Class: Non-dangerous goods
 - Label(s): –
- 14.4 Packing Group: –
- 14.5 Environmental hazards: –
- 14.6 Special precautions for user: –

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code: Not applicable.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

GB Regulations

The Ozone-Depleting Substances and Fluorinated Greenhouse Gases (Amendment etc.) (EU Exit)

Regulations 2019:

none

The Persistent Organic Pollutants (Amendment) (EU Exit) Regulations 2020:

none

Product name: SILKOLENE RSF 2.5

15.2 Chemical safety assessment:

No Chemical Safety Assessment has been carried out.

DIRECTIVE Control of Major Accident Hazards Regulations 2015:

The product does not fall into the scope of the Control of Major Accident Hazards Regulations 2015.

SECTION 16: Other information

Revision Information:

Vertical lines in the margin indicate an amendment.

Wording of the H-statements in section 2 and 3

EUH066	Repeated exposure may cause skin dryness or cracking.
H225	Highly flammable liquid and vapor.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.

Other information:

The classification complies with the current GB lists; however, it has been supplemented with expert literature information and information provided by/about our company. The following evaluation methods were used: On the basis of test data; Calculation Method; Bridging Principle "Substantially similar mixtures"; Expert Judgement

Revision Date:

11.01.2023

Disclaimer:

The data contained in this safety data sheet are based on our current knowledge and experience and are given to the best of our knowledge and belief. It characterizes the product only with regard to safety requirements for handling, transport and disposal. The data do not describe the product's properties (tech. product specification). Neither should any agreed property nor the suitability of the product for any specific technical application be deduced from the data contained in this safety data sheet. Modifications on this document are not allowed. The data are not transferable to other products. In the case of mixing the product with other products or in the case of processing, the data in this safety data sheet are not necessarily valid for the new-made material. It is the responsibility of the recipient of the product to observe federal, state and local law. Please contact us to obtain up-to-date safety data sheets. This document was issued electronically and has no signature.