

OWNER'S MANUAL

KTM 50SX (OEM CAP)

120-021-155-051



INTRODUCTION

This fork cartridge kit uses the original top cap supplied with the KTM 65SX forks. As such, both compression and rebound damping, as well as spring preload, cannot be adjusted due to the construction of the OEM top caps.

The adapters and accompanying spacers have been designed to place the damping adjusters in the middle of the total adjustment range (equivalent to 16 clicks), and the spring is preloaded to 3mm of compression.

RECOMMENDED SETTINGS	
Fork stroke	205mm
Air gap/Oil level	140mm
Fork oil	5wt.
Spring rate	29.5-330-VAR
Comp damping	16 Clicks (NON-ADJUSTABLE)
Reb damping	16 Clicks (NON-ADJUSTABLE)
Fork position	See Manufacturer's Specification.

ADJUSTMENT

This fork cartridge kit uses the original top cap supplied with the KTM 50SX forks. As such, both compression and rebound damping, as well as spring preload, cannot be adjusted due to the construction of the OEM top caps.

The adapters and accompanying spacers have been designed to place the damping adjusters in the middle of the total adjustment range (equivalent to 16 clicks), and the spring is preloaded to 3mm of compression.

SERVICE

K-Tech Suspension Ltd recommend that this product is serviced every 40 hours of use. It is very important that this product is serviced by an authorised dealer, as there are special tools required to guarantee correct performance of this product. K-Tech Suspension Ltd cannot be held responsible for any damage caused to/by the product if a service is overdue or was not conducted by an authorised dealer.

www.ktechsuspension.com/service-centres-and-partners



www.ktechsuspension.com

Contact your local K-Tech dealer for more details at
www.ktechsuspension.com/service-centres-and-partners