

Product Information

MOVING YOUR WORLD



SILKOLENE PRO FST

Fuel system treatment for petrol engines

Description

SILKOLENE PRO FST is a multi-functional fuel treatment. It protects against cold start wear, protects the fuel system from corrosion and keeps the injectors; intake systems and carburettors free from deposit build up ensuring optimum performance. It is very effective against carburettor icing in low temperature environments, and combats starting problems, stalling and rough running at low engine revs.

Application

SILKOLENE PRO FST can be used in leaded and unleaded fuel and in both 2 and 4-stroke engines. It reduces the incidence of pre-ignition and also enhances the fuel's octane rating to a small extent.

Advantages

- Recommended mix ratio:-
- SILKOLENE PRO FST is recommended to be used at a concentration of 1% to 2%
- For 1% mix 100 parts fuel to 1 part PRO FST
- For 2% mix 50 parts fuel to 1 part PRO FST.
- Multifunctional performance, wear protection, deposit protection and corrosion protection
- SILKOLENE PRO FST is compatible with catalytic converters
- Synthetic ester technology provides protection to metallic parts of the engine where the lube oil cannot reach
- Provides protection during periods of inactivity

Specifications

- -

Approvals

- -

FUCHS Recommendations

- -

Product Information

MOVING YOUR WORLD



Notes

The information contained in this product information is based on the experience and know-how of FUCHS LUBRICANTS (UK) plc in the development and manufacturing of lubricants and represents the current state-of-the-art. The performance of our products can be influenced by a series of factors, especially the specific use, the method of application, the operational environment, component pre-treatment, possible external contamination, etc. For this reason, universally valid statements about the function of our products are not possible.

Our products must not be used in aircraft or spacecraft. Our products may be used in manufacture of components for aircraft or spacecraft if they are removed without residue from the components prior to assembly into the aircraft or spacecraft.

The information given in this product information represents general, non-binding guidelines. No warranty expressed or implied is given concerning the properties of the product or its suitability for any given application. We therefore recommend that you consult a FUCHS LUBRICANTS (UK) plc application engineer to discuss application conditions and the performance criteria of the products before the product is used. It is the responsibility of the user to test the functional suitability of the product and to use it with the corresponding care.

Our products undergo continuous improvement. We therefore retain the right to change our product program, the products, and their manufacturing processes as well as all details of our product information sheets at any time and without warning, unless otherwise provided in customer-specific agreements. With the publication of this product information, all previous editions cease to be valid. Any form of reproduction requires express prior written permission from FUCHS LUBRICANTS (UK) plc.

© FUCHS LUBRICANTS (UK) plc. All Rights reserved.