

Silkolene[®]

SILKOLENE SCOOT 4 10W-40

4-Stroke engine oil for scooters and mopeds

Description

SILKOLENE SCOOT 4 10W-40 is a 10W-40 grade oil specifically designed for 4-stroke Scooters. The formulation provides exceptional anti-corrosion and anti-wear performance, even under extreme temperatures and conditions as well as offering excellent shear stability, giving outstanding stay-in-grade performance.

Application

SILKOLENE SCOOT 4 10W-40 is ideal for use in all modern high performance, free revving 4-stroke scooter engines. These features combine to ensure complete reliability, easy starting and all-round user friendly operation.

Advantages

- Designed specifically for Scooters
- Good anti-wear and corrosion protection
- Maintains viscosity during use

Specifications / Approvals

- API SL
- JASO MA & MA2

Product Information



Further Information

Typical Data: SILKOLENE SCOOT 4 10W-40

Characteristics	Test Method	Unit	
SAE Rating			10W/40
Specific Gravity at 15°C	IP160		0.881
Kinematic Viscosity @ 40°C	IP71	mm ² /s	90.6
Kinematic Viscosity @ 100°C	IP71	mm ² /s	14.28
Viscosity Index (VI)	IP226		163
Pour point	IP15	°C	-34
Flash Point (Closed Cup)	IP34	°C	180

Updated Nov 2019 ABUK

FUCHS LUBRICANTS (UK) plc
New Century Street, Hanley
Stoke-on-Trent, Staffordshire, ST1 5HU

Tel +44 (0)1782 203700
contact-uk@fuchs.com



Health, Safety and Environment - information is provided for products in the relevant Safety Data Sheet. This provides guidance on potential hazards, precautions and first-aid measures, together with environmental effects and disposal of used products. While the information and figures given here are typical of current production and conform to specification, minor variations may occur. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of the products.