

# Product Information

MOVING YOUR WORLD



## SILKOLENE QUAD ATV & UTV SAE 5W-40

Fully synthetic 4-stroke engine oil for modern highly loaded quad bikes, ATVs & UTVs.

### Description

SILKOLENE QUAD ATV & UTV SAE 5W-40 is a High Performance, fully synthetic 4-stroke engine oil specifically designed for modern ATVs, UTVs and quad bikes. SILKOLENE QUAD ATV & UTV SAE 5W-40 utilises high-performance synthetic base oils and additives to offer excellent anti-wear, anti-corrosion and stay-in-grade performance across a wide temperature range. SILKOLENE QUAD ATV & UTV SAE 5W-40 uses a balanced formulation to ensure the proper operation of oil-immersed clutches and other driveline components.

### Application

SILKOLENE QUAD ATV & UTV SAE 5W-40 is recommended for all ATVs, UTVs and quad bikes where SAE 5W-40 oils are specified and can also be used in some engines where SAE 10W-40 and 15W-40 are specified. SILKOLENE QUAD ATV & UTV SAE 5W-40 is suitable for both air- and liquid-cooled engines. SILKOLENE QUAD ATV & UTV SAE 5W-40 is miscible and compatible with conventional, branded engine oils. However, mixing with other engine oils should be avoided in order to fully exhaust this product's benefits. A complete oil drain is recommended when converting to SILKOLENE QUAD ATV & UTV SAE 5W-40. For information on product safety and proper disposal please refer to the latest Material Safety Data Sheet.

### Advantages

- Specifically designed for 4-stroke engines fitted with wet clutches.
- Outstanding wet clutch performance as per JASO MA2 standard leading to smooth gear changes and maximum power transmission.
- Outstanding gear wear and pitting protection.
- Outstanding engine wear protection.
- Outstanding protection against high-temperature deposits resulting in a clean engine and a long engine life.
- Provides substantially better corrosion protection, a better oxidation/nitration resistance and a lower volatility than conventional products.

### Specifications

- ACEA A3/B3
- API SN

### Approvals

- JASO MA2

### FUCHS Recommendations

- -

# Product Information

*MOVING YOUR WORLD*



## TYPICAL CHARACTERISTICS

---

Density at 15°C	DIN 51757	0.857 g/ml
Kinematic Viscosity at 40°C	DIN 51562-1	85.9 mm <sup>2</sup> /s
Kinematic Viscosity at 100°C	DIN 51562-1	14.4 mm <sup>2</sup> /s
Viscosity Index	DIN ISO 2909	174
CCS Viscosity at -30°C	ASTM D 5293	6,250 mPas
Closed Flash Point	ASTM D93	210 °C
Pour Point	DIN ISO 3016	-35 °C
Product Dyeing		none

# Product Information

*MOVING YOUR WORLD*



## Notes

The information contained in this product information is based on the experience and know-how of FUCHS LUBRICANTS (UK) plc in the development and manufacturing of lubricants and represents the current state-of-the-art. The performance of our products can be influenced by a series of factors, especially the specific use, the method of application, the operational environment, component pre-treatment, possible external contamination, etc. For this reason, universally valid statements about the function of our products are not possible.

Our products must not be used in aircraft or spacecraft. Our products may be used in manufacture of components for aircraft or spacecraft if they are removed without residue from the components prior to assembly into the aircraft or spacecraft.

The information given in this product information represents general, non-binding guidelines. No warranty expressed or implied is given concerning the properties of the product or its suitability for any given application. We therefore recommend that you consult a FUCHS LUBRICANTS (UK) plc application engineer to discuss application conditions and the performance criteria of the products before the product is used. It is the responsibility of the user to test the functional suitability of the product and to use it with the corresponding care.

Our products undergo continuous improvement. We therefore retain the right to change our product program, the products, and their manufacturing processes as well as all details of our product information sheets at any time and without warning, unless otherwise provided in customer-specific agreements. With the publication of this product information, all previous editions cease to be valid. Any form of reproduction requires express prior written permission from FUCHS LUBRICANTS (UK) plc.

© FUCHS LUBRICANTS (UK) plc. All Rights reserved.