



# PRODUCT DATA SHEET



---

## BEL-RAY<sup>®</sup> FIBER FILTER OIL

**Bel-Ray Fiber Filter Oil** was specifically developed for superior performance with all fiber/gauze type air filters. **Bel-Ray Fiber Filter Oil** is the superior trapping medium needed to obtain maximum efficiency from today's fiber/gauze type air filters. It traps and holds contaminants. It will not gum or clog and it does not restrict airflow. **Bel-Ray Fiber Filter Oil** is water resistant and will not run off.

### *Applications*

---

- ◆ For 2-stroke or 4-stroke engines in motorcycles or ATVs with fiber/gauze air filters
- ◆ Equally suitable for air-cooled or liquid-cooled engines
- ◆ For best performance and protection over the entire rpm range, rpm from idle to high revs
- ◆ Use when maximum contaminant-free intake airflow is to be maintained

### *Features and Benefits*

---

- |                      |   |
|----------------------|---|
| ◆ Superior tackiness | Traps the finest dust and sand for reduced abrasive engine wear. Maintains maximum filter efficiency. Maximum airflow for superior power. |
| ◆ Waterproof         | Will not wash off in the rain or during washing. Ensures continued protection in wet conditions for reduced wear and longer engine life.  |
| ◆ Easy to use        | The aerosol spray simplifies application. Red color makes it easy to see coverage for maximum performance. No mess or spills.             |
| ◆ Fast drying        | Fast and easy application.  |

### *General Description*

---

**Bel-Ray Fiber Filter Oil** is recommended for all fiber/gauze air filters. It is fast drying and easy to use. **Bel-Ray Fiber Filter Oil** will maintain top filter performance allowing maximum flow of clean air. By eliminating trapping airborne contaminants, **Bel-Ray Fiber Filter Oil** provides maximum power and performance, and protection for longer engine life.

### *Product No. 99170*

Page 1 of 2

6/1/2010

*With continual research and development, Bel-Ray Company, Inc. reserves the right to change the information contained herein. The Company is not responsible for misuse or misapplication of its products.*

# BEL-RAY<sup>®</sup> FIBER FILTER OIL

## Product No. 99170

### Application Instructions

---

Wear rubber gloves and eye protection. Remove filter. Clean according to manufacturer's instructions. Spray **Bel-Ray Fiber Filter Oil** on evenly. Let stand allowing oil to permeate filter. Check for dry (white) spots; if white areas appear reapply **Bel-Ray Fiber Filter Oil**. Uniform red color indicates proper application.

Prior to installing the filter, allow a few minutes for drying before starting the engine. For maximum penetration more than one application may be necessary. Dispose of empty containers in a responsible manner.

**Caution:**      *Use in a well-ventilated space. Product is flammable and should be used with appropriate caution.*

*Do not spray on a hot surface or in proximity to flames or open fire.*

*Do not puncture or incinerate container, even when empty.*

*Always wear safety glasses when using this product.*

*Keep container away from heat.*