

Silkolene®

SILKOLENE SCOOT SPORT 2

Electrosyntec technology ester based low smoke 2-Stroke oil for scooters and mopeds

Description

SILKOLENE SCOOT SPORT 2 with Electrosyntec uses electrostatic forces to bond low friction molecules to stressed metal surfaces, releasing hidden power and ensuring long-term performance retention. This advanced low smoke 2-stroke engine oil reduces engine wear and maintains optimum power while providing outstanding resistance to ring sticking, plug fouling and pre-ignition.

Application

SILKOLENE SCOOT SPORT 2 is suitable for all two stroke scooters and mopeds with or without autolube systems.

SILKOLENE SCOOT SPORT 2 is compatible with all types of fuel and is exceptionally clean burning.

Advantages

- Reduces friction and engine wear
- Releases and helps maintain optimum power
- Provides outstanding resistance to ring sticking, plug & port fouling and pre-ignition

Specifications

- | | |
|--------|---------|
| • JASO | FC / FD |
| • ISO | L-EGD |
| • API | TC |

Further Information

Typical Data: SILKOLENE SCOOT SPORT 2

Characteristics	Test Method	Unit	Result
SAE Rating			30
Appearance	Visual		
Specific Gravity at 15°C	IP160		0.868
Kinematic Viscosity @ 40°C	IP71	mm ² /s	75.58
Kinematic Viscosity @ 100°C	IP71	mm ² /s	10.41
Viscosity Index (VI)	IP226		124
Flash Point (Closed Cup)	IP34	°C	86
Pour point	IP15	°C	-21

Reviewed 21/04/2020 AB