



PRODUCT DATA SHEET



BEL-RAY[®] SUPER DOT 4 BRAKE FLUID

Bel-Ray Super DOT 4 Brake Fluid exceeds FMVSS Sec. 571.116 DOT 4 motor vehicle brake fluid, SAE J1703 and ISO 4925 specifications. **Bel-Ray Super DOT 4 Brake Fluid** mixes with all fluids meeting DOT 3 and 4 specifications. **Bel-Ray Super DOT 4 Brake Fluid** is for use in all drum or disc brake systems and hydraulic clutches, except systems using mineral-based fluids (LHM). Boiling Point: Dry 230°C (446°F), Wet 155°C (311°F).

Applications

- ◆ When DOT 3 or DOT 4 product is specified for hydraulic brake systems

Features and Benefits

- | | |
|------------------------|--|
| ◆ High vapor point | Resists vapor formation to minimize the potential for “vapor lock” and the subsequent loss of braking power. |
| ◆ High boiling point | Eliminates brake fade for superior performance. |
| ◆ High compatibility | Compatible with all seal materials normally used in brake systems. |
| ◆ Corrosion protection | Special formulation with inhibitors against rust and chloride corrosion. |

General Description

Bel-Ray Super DOT 4 Brake Fluid is formulated to meet all DOT 3 and 4 specifications. It is compatible with all DOT 3 and DOT 4 type products.

Product No. 99480

Page 1 of 2

6/1/2010

With continual research and development, Bel-Ray Company, Inc. reserves the right to change the information contained herein. The Company is not responsible for misuse or misapplication of its products.

BEL-RAY[®] SUPER DOT 4 BRAKE FLUID

Product No. 99480

Application Instructions

Follow vehicle manufacturer's recommendations when adding brake fluid. Keep brake fluid clean and dry. Contamination with dirt, water, petroleum products or other materials may result in brake failure or costly repairs. Store brake fluid only in its original container. Keep container clean and tightly closed to prevent absorption of moisture.

For best results drain and replace the brake fluid once a year. Flush and refill system with fresh **Bel-Ray Super DOT 4 Brake Fluid**. Bleed the hydraulic system as recommended by the manufacturer. Check and replace damaged seals and dust protectors if needed. Dispose of empty containers in a responsible manner.